

Plastic Ceiling Receptacle Lampholders

Medium Base 660W 250V 250W 250V








4.75" **1173-6**



768-2



788



4.50 **865**



Top Wire

Plastic Ceiling Receptacle Lampholders

Features:

- · Meets all UL 496 requirements.
- Molded of high-temperature, thermoset plastic to prevent discoloration and reduce breakage.
- Mounts on 4" outlet boxes with breakout for 3 1/4" box mounting.
- Leads are 6" 105°C insulated stranded #16, stripped 3/4".
- Pull chain devices include ball chain, 3' of cord, connector and endbell.
- · Top wire versions have terminal screws

- backed out ready for wiring without removing interior.
- Push wire terminals are top wired with two push-in terminals and two screw terminals for continuous wiring.
- Sockets available in two piece version to permit interior replacement, dust ring protects against plaster and dirt.
- Shade grooves provided on two piece units.
- · Made in USA.

Med	Catalog No.					
Rati	ng					
W	V	Description	Terminals	Switch	Color	
660	250	One Piece	4 Top Wire Screws	Keyless	White	1174W
660	250	One Piece	2 Top Wire Screws	Pull Cord	White) 1173W
660	250	One Piece	6" Leads	Keyless	White	1174-6W
660	250	One Piece	6" Leads	Pull Cord	White	1173-6W
660	250	Two Piece	Push Wire/ Top Wire	Keyless	Brown	768B
660	250	Two Piece	Push Wire/ Top Wire	Keyless	White	768W
660	250	Two Piece	2 Screws	Keyless	White	768-2W
660	250	Two Piece	6" Leads	Keyless	White	768-6W

Med	Catalog No					
Rating W V Description			Terminals	Switch	Color	
250	250	Two Piece	Push Wire/ Top Wire	Pull Chain	White	759W-CD
250	250	Two Piece	6" Leads	Pull Cord	Brown	788B
250	250	Two Piece	6" Leads	Pull Cord	White	788W
250	250	Two Piece w/ 15A 125V 2P2W Outlet	Push Wire/ Top Wire	Pull Cord	White	860W
250	250	Two Piece w/ 15A 125V 2P3W Outlet	Push Wire/ Top Wire	Pull Cord	White	865W
250	250	Two Piece w/ 15A 125V 2P3W Outlet	Push Wire/ Top Wire	Pull Cord	Brown	865B



Lampholders