



Actual

**Catalog Number:** 162LR-B-5240  
**Product ID:** 7TAA121100R0190  
**UPC Number:** 07511418653  
**Status:** Active

15kV 200 Amp, Loadbreak Elbow Connector with Test Point, .635 inch - .905 inch Cable Insulation Diameter, 1/0 Stranded Wire Size, Bi-Metal Compression Lug

## UNSPSC Specifications

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Loadbreak Elbow Connector with Test Point
Special Features	15kV, 200 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation. Provision for ground wire connection. Wide cable range with minimum number of sizes. Long bi-metal compression lug is standard. Non-corrosive capacitive test point.
Application	15kV, 200 Amp
Standard	ANSI/IEEE Standard 386
Size	7.76 inch (197.1 mm) X 9.03 inch (229.4 mm), 2.92 inch (74.2 mm) Diameter
Material	EPDM Rubber
Color	Black
Voltage Rating	15 kV
Amperage Rating	200 Amps
Insulation	Yes
Environmental Conditions	All Weather Conditions
Consist Of	1 Elbow Connector Housing, 1 Compression Lug, 1 Probe, 1 Probe Wrench, 1 Tube of Lubricant, 1 Crimp Chart, V.D. Cap-Peroxide, 1 Installation Instructions sheet.

## Packaging

Inner Quantity	1
Outer Quantity	15
Outer Dimensions (inches)	10.5x19.12x12.5
Weight Uom	2.12 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)