


# B<sub>4</sub>

## SINGLE-GANG BOXES DIE CAST ALUMINUM



### 2" DEEP, WITH LUGS THREE THREADED OUTLETS 4 1/2" x 2 3/4"



5320-0 to 5320-7  
5324-0 to 5324-5

RACO NO.	CUBIC IN.	DESCRIPTION		PKG. TYPE	STD. PKG.	UPC BAR CODE
		COLOR	OUTLETS			
5320-0	17.5	Gray	3 - 1/2"	Shrink	20	■■■■
5320-1	17.5	White	3 - 1/2"	Shrink	20	■■■■
5320-2	17.5	Bronze	3 - 1/2"	Shrink	20	■■■■
5320-5	17.5	Gray	3 - 1/2"	Carded	6	■■■■
5320-6	17.5	White	3 - 1/2"	Carded	6	■■■■
5320-7	17.5	Bronze	3 - 1/2"	Carded	6	■■■■
5324-0	17.0	Gray	3 - 3/4"	Shrink	20	■■■■
5324-5	17.0	Gray	3 - 3/4"	Carded	6	■■■■


### 2" DEEP, WITH LUGS FOUR THREADED OUTLETS 4 1/2" x 2 3/4"




5321-0 to 5321-7,  
5330-0

RACO NO.	CUBIC IN.	DESCRIPTION		PKG. TYPE	STD. PKG.	UPC BAR CODE
		COLOR	OUTLETS			
5321-0	17.0	Gray	4 - 1/2"	Shrink	20	■■■■
5321-1	17.0	White	4 - 1/2"	Shrink	20	■■■■
5321-2	17.0	Bronze	4 - 1/2"	Shrink	20	■■■■
5321-5	17.0	Gray	4 - 1/2"	Carded	6	■■■■
5321-6	17.0	White	4 - 1/2"	Carded	6	■■■■
5321-7	17.0	Bronze	4 - 1/2"	Carded	6	■■■■
5330-0	16.5	Gray	4 - 3/4"	Shrink	20	■■■■

### 2" DEEP, WITH LUGS FIVE THREADED OUTLETS 4 1/2" x 2 3/4"



5322-0, 5331-0



5323-0, 5332-0

RACO NO.	CUBIC IN.	DESCRIPTION		PKG. TYPE	STD. PKG.	UPC BAR CODE
		COLOR	OUTLETS			
5322-0	16.5	Gray	5 - 1/2"	Shrink	20	■■■■
5331-0	16.0	Gray	5 - 3/4"	Shrink	20	■■■■
5323-0	17.0	Gray	5 - 1/2"	Shrink	20	■■■■
5332-0	16.5	Gray	5 - 3/4"	Shrink	20	■■■■

# B<sub>1</sub>



## BELL WEATHERPROOF BOXES, COVERS & LIGHTING

**(4) Device or Equipment Fill.** For each yoke or strap containing one or more devices or equipment, a double volume allowance in accordance with Table 370-16(b) shall be made for each yoke or strap based on the largest conductor connected to a device(s) or equipment supported by that yoke or strap.

**(5) Equipment Grounding Conductor Fill.** Where one or more equipment grounding conductors enters a box, a single volume allowance in accordance with Table 370-16(b) shall be made based on the largest equipment grounding conductor present in the box. Where an additional set of equipment grounding conductors, as permitted by Section 250-74, Exception No. 4, is present in the box, an additional volume allowance shall be made based on the largest equipment grounding conductor in the additional set.

GENERAL INFORMATION	B1-B3
BELL BOXES, EXTENSIONS & ADAPTERS	B4-B11
SPECIALTY BOXES	B12-B13
RAYNTITE II COVERS	
RAYNTITE COVERS	B14-B19
DEVICE & SWITCH COVERS	
DEVICE KITS & ACCESSORIES	B20-B27
CLUSTER COVERS	B28
LAMPHOLDERS & LIGHTING KITS	B29-B33
GARDEN LIGHTS	B34
REPLACEMENT GLOBES, PHOTOCELLS & HARDWARE	B35-B36
ACCESSORIES & PARTS	B37-B39

# B<sub>2</sub>

## STANDARDS, 1996 NATIONAL ELECTRICAL CODE®

### Article 410-57(b) Wet Locations.

**(b) Wet Locations.** A receptacle installed in a wet location shall be in a weatherproof enclosure, the integrity of which is not affected when the attachment plug cap is inserted.

*Exception: An enclosure that is not weatherproof when an attachment plug cap is inserted shall be permitted where a receptacle is installed in a wet location for use with portable tools or other portable equipment normally connected to the outlet only when attended.*

Reprinted with permission from the NFPA 70-1996, *National Electrical Code®* Copyright© 1995, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the NFPA on the reference subject which is represented only by the standard in its entirety. *National Electrical Code®* and *NEC®* are registered trademarks of the National Fire Protection Association, Quincy, MA.

### BELL PRODUCTS: GENERAL FEATURES AND BENEFITS

Bell Weatherproof products all offer these features and benefits:

- Rugged seamless die cast construction that will not allow entry of moisture
- Reinforced connector outlets to provide a secure mechanical installation
- State-of-the-art powder coat paint for maximum weatherability and scratch resistance
- Multi-lingual instructions provided with every product
- Installation hardware and ground screws included where applicable
- Shrink-wrap packaging that keeps all components together
- UPC-A barcoding to help lower transaction costs

Refer to the following pages for more specific information about Bell products.

