

Cable Adapter

By Hubbell Power Systems
Catalog # [635CAP](#)



35kV 600/900A Cable Adapter, Cable Insulation Diameter
Range = 1.530 - 1.640 Inches

Features

- Meets or Exceeds IEEE Std. 386 and IEEE Std. 592 requirements
- Interchangeable with other products meeting the same requirements
- Stepped design

General

| | |
|----------------|---------------|
| Catalog Number | 635CAP |
| Type | Cable Adapter |
| UPC | 096359833840 |

Dimensions

| | |
|--------------------------------------|---------|
| Cable Insulation Diameter Maximum | 1.64 in |
| Cable Insulation Diameter Minimum | 1.53 in |

Electrical Ratings

| | |
|------------------------------|--------|
| AC Withstand Voltage (1 min) | 50 kV |
| Basic Impulse Level | 200 kV |

| | |
|-------------------------------------|----------------|
| Corona Extinction (3pC) kV Class | 26 kV 35 kV |
|-------------------------------------|----------------|

Conductor Related

| | |
|------------------------------------|-------------|
| Cable Insulation Diameter Range | 1.53 - 1.64 |
|------------------------------------|-------------|

Logistics

| | |
|------------------|------|
| Pallet Quantity | 1536 |
| Standard Package | 12 |

Product Assets

- [Catalogs - Cable Accessories](#)
- [Installation Manuals - IS635BT Installation & Operating Instructions](#)
- [Sales Drawings - 35kV Cable Adapters](#)
- [SDS - Safety Data Sheet - Versilube G661 Silicone Compound Specifications - 635CAP](#)
- [Test Documents - 35kV Class 600 Deadbreak Connector Test Report](#)
- [Video - Grease Best PRactices](#)