



Powering Business Worldwide

pe.eaton.com

Power Supply

PSG120E

UPC:786685215440

Dimensions:

- **Height:** 4.53 IN
- **Length:** 4.76 IN
- **Width:** 1.97 IN

Weight:.81 LB

Notes:Ratings for single-phase are at 115V. 0 Hz at DC input.

Warranties:

Specifications:

- **Special Features:** Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection, finger-safe cover
- **Operating Temperature:** -20° to 75°C
- **Wattage:** 120W
- **Enclosure Material:** Aluminum
- **Frequency Rating:** 47-63 Hz
- **Input Voltage:** 100-240V
- **Output Voltage:** 24 Vdc
- **Rated Operational Current:** 1.4A input, 5A output, less than 80A inrush, 7.5A surge
- **Series:** PSG
- **Terminals:** Heavy-duty screw
- **Phase:** Single-phase
- **Voltage Rating:** 85-264V, 120-375 Vdc

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG120E AutoCAD 2D Footprint \(mm\)](#)
- [Installation Instructions for PSG120E Power Supply](#)



- [Eaton's PSG Series Power Supplies](#)
- [Eaton Specification Sheet - PSG120E](#)

Certifications:

- UL 508
- cULus/UL 60950-1
- CSA Certified
- IEC Rated
- cUL Certified
- EN Listed

Product compliance:

- German Safety
- CE Marked
- RoHS Compliant