Thomas&Betts



Actual



Representative

Catalog Number: Product ID: UPC Number: Status:

T27SA-G 7TAA087800R0002 70450841001 Active

PVC Coated Conduit Body, T Shape, Form 7, Size 3/4 Inch/21 Metric, Aluminum, Dark Gray

- A minimum of .040 inch PVC coating is bonded to the exterior.
- Covers are coated with a molded flange to seal the conduit body while the conduit body is molded with a flat surface on its opening to seal with the cover.
- · Ocal pressure-sealing sleeves on all threaded hubs.
- Ocal conduit bodies are shipped with a cover and encapsulated stainless steel screws.
- Bodies are designed with a flat back, allowing more cubic inch capacity. The flat back also keeps the body more stable during installation, requiring fewer conduit straps.
- · Provide openings for making splices and taps in conductors
- Connect conduit sections
- · Provide taps for branch conduit runs
- · Make 90° bends in conduit runs
- · Provide for access to conductors for maintenance and future system changes

UNSPSC Specifications

ontor oo opcombations	
UNSPSC	39131708 Electrical conduit fitting body
IGCC	5563 Electrical conduit fitting body
Brand Name	Ocal
Туре	Form 7 Conduit Body
Special Features	The Conduit Body and Cover are Double Coated
	with a Nominal .002 In. Blue Urethane on Both The
	Interior and Exterior, Before PVC Coating is Applied
Application	Act As Pull Outlets for Conductors Being Installed
Standard	UL E2969, CSA
Hub Size	3/4 Inch/21mm
Form	7
Length	6.20 Inch
Width	2.00 Inch
Height	2.60 Inch
Material	Aluminum
Finish	PVC Coated
Color	Dark Gray
Packaging	

Inner Dimensions (inches)	XX
Outer Quantity	10
Outer Dimensions (inches)	15.2x13.65x8.5
Weight Uom	0.9 lbs. Each

Documents / Support Tools

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website
Support/Tools 1	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd.

T&B Technical Support MS 3B-50 Hours: 7AM - 6PM CDT Monday-Friday



Memphis, TN 38125 www.tnb.com 8155 T&B Blvd. Memphis, TN 38125 Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com