

Description: 16 AWG 2/C AUDACIOUS HTS. UL CL3R OR CMR C(UL)US FT4

Specifications: UL Standards 13, & 444; NEC Articles 725 & 800, CSA C22.2 NO. 214

Construction:

Conductor 16 AWG 65/34 Stranded OFBC
Insulation PVC
Insulation Thickness 0.015" nom.
Insulation Colors Blk,Red
Insulation Diameter 0.086 nom.
Lay Length 3.5" nom.

Jacket PVC
Jacket Color Lt. Purple or White
Jacket Thickness 0.035" nom.
Outside Diameter 0.262" nom.
Legend (Ink Print) HONEYWELL AUDACIOUS OXYGEN FREE P/N 5473 2C16 E175106 (UL) CL3R
OR CMR C(UL)US FT4 75C SUN RES (RoHS) W/O#XXXXXX-XXXXXX XXXXX FT
- L C R LR RR RM# A B C D E F 1 2 3 4 5 6 7 8 9 (PAT PEND)

Properties

Temperature Rating -20 to 75 °C
Operating Voltage 300 Volts max.
Capacitance 22 pf/ft nom.
Impedance 85 Ohms nom.
DC Resistance 4.10 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 2556 (FT4)