

Rittal – The System.

Faster – better – everywhere.

Enclosure Heaters without fan – SK 3105.370

Date : Jan 21, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure Heaters without fan – SK 3105.370

created: 21.01.2017 build on www.rittal.com/us-en



Product description

Supply includes: PTC heater
Quick-connection terminal
Fasteners

Note: For precise temperature control inside the enclosure, we recommend using the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, hygrostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.

Note on Model No.: Special voltages available on request. We reserve the right to make technical modifications.

Product features

Continuous thermal output at 10°C: 130 W - 150 W

Rated operating voltage: 110 V - 240 V, 1~, 50 Hz/60 Hz

Dimensions: Height: 180 mm (7.1 ")
Width: 90 mm (3.5 ")
Depth: 75 mm (3 ")

Pre-fuse: Miniature circuit-breaker/fuse: 4 A

Packaging unit: 1 pc(s).

Weight/packaging unit: 0.9 kg (2 lb.)

EAN: 4028177638679

Customs tariff number: 85162999

ETIM 6.0: EC000737

ETIM 5.0: EC000737

eCl@ss 8.0/8.1: 27180710

eCl@ss 7.0/7.1: 27180710

eCl@ss 6.0/6.1: 27180710

eCl@ss 5.1/5.1.4: 27180710

Approvals

Approvals: Approval overview
C-UR
CSA
UR
UR + C-UR
VDE

Declarations: Declaration of conformity