Beam/Purlin

Hangers/Hanging Systems

Stud Wall

Communication/ Low Voltage

Dry Wall

Acoustical

Miscellaneous

Codes & Standards Sizing Information Reference

**Push-Fit Conduit Clips** 



- No fastener required to retain conduit
- Static load capacity:
  - 25 lbs. in vertical position
  - 15 lbs. in horizontal position
- Available with 1/4" non-threaded mounting hole

| Part Number | Fits EMT<br>(In.) | Fits Rigid/IMC<br>(In.) | Std.<br>Pkg.<br>Qty. |
|-------------|-------------------|-------------------------|----------------------|
| P8P         | 1/2               | _                       | 100                  |
| P12P        | 3/4               | 1/2                     | 100                  |
| P16P        | 1                 | 3/4                     | 100                  |



## **Conduit Clamps with Bolt**



- Conduit hanger available for 1/2" 4" conduit
- Bolt and nut (Phillips/flathead) provide positive securing feature
- · Available with threaded and non-threaded mounting hole



| Part Number | Fits<br>EMT<br>(In.) | Fits Rigid/<br>IMC<br>(In.) | Mounting Hole<br>(In.) | Std.<br>Pkg.<br>Qty. |
|-------------|----------------------|-----------------------------|------------------------|----------------------|
| PCD0B       | 1/2                  | 3/8 – 1/2                   | 1/4 non-threaded       | 100                  |
| PCD1B       | 3/4                  | 3/4                         | 1/4 non-threaded       | 100                  |
| PCD2B       | 1                    | 1                           | 1/4 non-threaded       | 100                  |
| PCD2.5B     | 1 1/4                | _                           | 1/4 non-threaded       | 100                  |
| PCD3B       | 1 1/2                | 1 1/4                       | 1/4 non-threaded       | 100                  |
| PCD4B       | _                    | 1 1/2                       | 5/16 non-threaded      | 100                  |
| PCD5B       | 2                    | 2                           | 5/16 non-threaded      | 50                   |
| PCD6B       | 2 1/2                | 2 1/2                       | 5/16 non-threaded      | 50                   |
| PCD7B       | 3                    | 3                           | 5/16 non-threaded      | 25                   |
| PCD8B       | 3 1/2                | 3 1/2                       | 5/16 non-threaded      | 25                   |
| PCD9B       | 4                    | 4                           | 1/2 non-threaded       | 10                   |



