




## Conduit Bodies & Covers-PVC Coated T&B Catalog Number:


T18-4X-G

**UPC Number:** 70450802546

Status: Active

**Description:** 







Features	
	UL Listed Type 4X and NEMA 4X rating for excellent protection in wash down areas, as well as harsh outdoor environments exposed to moisture, rain, ice or snow.  Double coated superior corrosion protection, bodies and covers coated inside and out with .002 in. blue urethane, then exterior coated with a minimum of .040 in. PVC.
	PVC coated cast iron conduit body comes with mat- ed cast iron cover, injection molded with an inte- gral O-ring seal and stainless steel encapsulated screws.
Application	
	Act as pull outlets for conductors being installed Provide openings for making splices and taps in conductors
	Connect conduit sections
	Provide taps for branch conduit runs
	Make 90° bends in conduit runs
	Provide for access to conductors for maintenance
_	and future system changes
General	
Custom_Finish	f8t12
Trade Size (inches)	1/2
Material	Gray Iron
Finish	PVC Coated
Color	Dark Gray
Conduit Body Shape	Т
Dimension Information	
Dimension A (inches)	5 11/16
Dimension B (inches)	1 3/4
Dimension C (inches)	2 5/32
Dimension D (inches)	1
Dimension E (inches)	3 5/16
Technical Information	
Chemical Resistance Chart	Available on Website
	Available off vyebbite
Specifications	
Specifications	

Ocal Specification Guide-1995 Master Format-PDF	
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website
Packaging	
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	2.09 lbs. Each
Application Support	
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
Product Overview-Conduit Outlet Bodies	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General	Available on Website
Wiring	
NEC Table 8	Available on Website
Notes	
	Dimensional values are of uncoated conduit bodies.

## Certifications





File Nbr: E 2969

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com