

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings LCP, LC6, LI6, L7XP, L7XPR, L7X and L7XR.

CONSTRUCTION

Aluminum white sphere.

Polyester powder coat paint.

White narrow integral flange.

40 degree vertical tilt standard.

350 degree horizontal rotation.

INSTALLATION

Socket to trim interface.

Retaining clips riveted to top of reflector hold trim inside housing.

LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

WARRANTY

1-year limited warranty. Complete warranty terms located at

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.


Catalog Number
Notes
Type

6" Finishing Trim

CE1

EYEBALL

Narrow Flange



Specifications


Height: 6-1/2 (16.5)

Lamp opening: 5-7/8 (14.9)

Diameter: 7-5/8 (19.4)

Trim height when used with
Non-IC incandescent rough-in

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: CE1

CE1	
Series	Finish
CE1	(blank) White MW Matte white

Accessories: Order as separate catalog number.	
CRT6	6" goof ring, white

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30	LCP, LC6, LI6, L7X, L7XR, L7XPR, L7XR
		65 BR30	

CE1 6" Eyeball Full Reflector Trim

For BR and PAR reflector lamps, see lamp manufacturer's published raw lamp data for photometrics.