

Squeeze Connectors

For Flex • AC • MC cable.
Zinc die-cast.



L42



L421-L426





L427-L4210


CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
L42	34200	3/8	1/2	50	500	.937	.460	1.155	.530-.620	.400
L420*	34021	3/8	1/2	50	500	1.032	.460	1.155	.530-.620	.400 x .580
L421	34210	1/2	1/2	25	250	1.439	.420	1.420	.850-.910	.620
L422	34220	3/4	3/4	25	250	1.555	.440	1.570	1.100-1.135	.820
L423	34230	1	1	10	100	1.770	.560	1.860	1.255-1.375	.940
L424	34240	1-1/4	1-1/4	5	50	1.910	.630	2.240	1.550-1.610	1.240
L425	34250	1-1/2	1-1/2	5	50	2.125	.610	2.640	1.810-1.895	1.460
L426	34260	2	2	5	30	2.550	.690	3.155	2.260-2.485	1.935
L427	34270	2-1/2	2-1/2	5	5	2.890	.890	3.810	2.770-2.950	2.440
L428	34280	3	3	1	6	3.870	.985	4.320	3.170-3.560	2.980
L429	34290	3-1/2	3-1/2	1	6	4.265	1.000	4.860	3.630-4.155	3.478
L4210	34211	4	4	1	6	4.560	1.000	5.415	4.030-4.635	3.977

*L420 not listed for flexible metal conduit.

Refer to chart at end of Section E for a list of cable type S.




Sizes 3/8" - 2" are manufactured as shown above.



Sizes 2-1/2" - 4" are manufactured as shown above.


Squeeze Connectors with Insulated Throat

For Flex • AC • MC Cable.
Zinc die-cast.




CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
L421A	34212	1/2	1/2	25	250	1.500	.451	1.420	.850-.910	.620
L422A	34213	3/4	3/4	25	250	1.586	.471	1.570	1.100-1.135	.820
L423A	34214	1	1	10	100	1.800	.591	1.860	1.255-1.375	.940
L424A	34215	1-1/4	1-1/4	5	50	1.972	.692	2.240	1.550-1.610	1.240
L425A	34216	1-1/2	1-1/2	5	50	2.187	.672	2.640	1.810-1.895	1.460
L426A	34217	2	2	5	30	2.612	.752	3.155	2.260-2.485	1.935
L427A	34270	2-1/2	2-1/2	5	5	2.983	.983	3.810	2.770-2.950	2.440
L428A	34280	3	3	1	6	3.963	1.078	4.320	3.170-3.560	2.980
L429A	34290	3-1/2	3-1/2	1	6	4.358	1.093	4.860	3.630-4.155	3.478
L4210A	34211	4	4	1	6	4.653	1.093	5.415	4.030-4.635	3.977

Refer to chart at end of Section E for a list of cable types.



Sizes 3/8" - 2" are manufactured as shown above.



Sizes 2-1/2" - 4" are manufactured as shown above.



CABLE RANGES

Style	Part Number ST = SNAP-TITE*	K.O. $\frac{1}{2}$ lbs	Outer Diameter inches MC/AC	Throat Diameter	Number of Cables	Insulated Throat	Flexible Metal Conduit (FMC)			Armored Cable (AC)		Metal Clad Cable (MC)		
							Steel	Aluminum	Reduced Wall Aluminum	Steel	Aluminum	Aluminum Corrugated	Aluminum Corrugated	Aluminum Rectangular Continuous Corrugated
90° Two Screw Clamp Type Connectors	850	1/2	.440 - .750	.620	1	•	•	•	•	•	•	•	•	•
	850A	1/2	.440 - .750	.560	1	•	•	•	•	•	•	•	•	•
	850ST	1/2	.440 - .750	.620	1	•	•	•	•	•	•	•	•	•
	850AST	1/2	.440 - .750	.560	1	•	•	•	•	•	•	•	•	•
	851	1/2	.635-1.085	.620	1	•	•	•	•	•	•	•	•	•
	851A	1/2	.635-1.085	.560	1	•	•	•	•	•	•	•	•	•
	851 ST	1/2	.635-1.085	.620	1	•	•	•	•	•	•	•	•	•
	851 AST	1/2	.635-1.085	.560	1	•	•	•	•	•	•	•	•	•
	852	3/4	.830-1.380	.825	1	•	•	•	•	•	•	•	•	•
	852A	3/4	.830-1.380	.765	1	•	•	•	•	•	•	•	•	•
	853	1	1.330-1.570	1.025	1	•	•	•	•	•	•	•	•	•
	853A	1	1.330-1.570	.974	1	•	•	•	•	•	•	•	•	•
	854	1-1/4	1.625-1.940	1.375	1	•	•	•	•	•	•	•	•	•
	854A	1-1/4	1.625-1.940	1.294	1	•	•	•	•	•	•	•	•	•
	855	1-1/2	1.400-2.400	1.575	1	•	•	•	•	•	•	•	•	•
	855A	1-1/2	1.400-2.400	1.532	1	•	•	•	•	•	•	•	•	•
	856	2	1.400-2.400	2.030	1	•	•	•	•	•	•	•	•	•
	856A	2	1.400-2.400	2.007	1	•	•	•	•	•	•	•	•	•
	857	2-1/2	2.600-3.100	2.450	1	•	•	•	•	•	•	•	•	•
	857A	2-1/2	2.600-3.100	2.425	1	•	•	•	•	•	•	•	•	•
858	3	3.100-3.640	3.140	1	•	•	•	•	•	•	•	•	•	
858A	3	3.100-3.640	3.050	1	•	•	•	•	•	•	•	•	•	
859	3-1/2	3.380-4.220	3.540	1	•	•	•	•	•	•	•	•	•	
859A	3-1/2	3.380-4.220	3.960	1	•	•	•	•	•	•	•	•	•	
8510	4	3.730 - 4.550	3.540	1	•	•	•	•	•	•	•	•	•	
8510A	4	3.730 - 4.550	3.960	1	•	•	•	•	•	•	•	•	•	
Squeeze Connectors	L42	1/2	.530-.620	.400	1	•	•	•	•	•	•	•	•	•
	L420	1/2	.530-.620	.400 x .580	1	•	•	•	•	•	•	•	•	•
	L420ST	1/2	.530-.620	.400 x .580	1	•	•	•	•	•	•	•	•	•
	L421	1/2	.850-.910	.620	1	•	•	•	•	•	•	•	•	•
	L421A	1/2	.850-.910	.620	1	•	•	•	•	•	•	•	•	•
	L422	3/4	1.100-1.135	.820	1	•	•	•	•	•	•	•	•	•
	L422A	3/4	1.100-1.135	.820	1	•	•	•	•	•	•	•	•	•
	L423	1	1.255-1.375	.940	1	•	•	•	•	•	•	•	•	•
	L423A	1	1.255-1.375	.940	1	•	•	•	•	•	•	•	•	•
	L424	1-1/4	1.550-1.610	1.240	1	•	•	•	•	•	•	•	•	•
	L424A	1-1/4	1.550-1.610	1.240	1	•	•	•	•	•	•	•	•	•
	L425	1-1/2	1.810-1.895	1.460	1	•	•	•	•	•	•	•	•	•
	L425A	1-1/2	1.810-1.895	1.460	1	•	•	•	•	•	•	•	•	•
	L426	2	2.260-2.485	1.935	1	•	•	•	•	•	•	•	•	•
	L426A	2	2.260-2.485	1.935	1	•	•	•	•	•	•	•	•	•
	L427	2-1/2	2.770-2.950	2.440	1	•	•	•	•	•	•	•	•	•
	L427A	2-1/2	2.770-2.950	2.440	1	•	•	•	•	•	•	•	•	•
L428	3	3.170-3.560	2.980	1	•	•	•	•	•	•	•	•	•	

(Continued next page)