



### T9, T12 RAPID START LAMPS

#### Circline T9 Rapid Start Lamps

Nominal Wattage	Bulb	Outside Diameter (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life 3hrs/start	CCT (K)	CRI	Initial Lumens 25°C/77°F	Notes
20	T9	6.25 - 6.75	4-Pin	20112	FC6T9/DCW/RS	6	8000	4100	80	750	3,12,13,15,17
				20156	FC6T9/CW/RS	12	8000	4200	60	750	3,12,13,15,17
22	T9	8.00 - 8.50	4-Pin	20088	FC8T9/WW/RS	12	12000	3000	52	1050	3,12,13,15,17
				20113	FC8T9/DCW/RS	6	12000	4100	80	1050	3,12,13,15,17
				20209	FC8T9/DSW/RP	6	12000	3000	70	1100	3,12,13,15,17
				20148	FC8T9/CW/RS	12	12000	4200	60	1050	3,12,13,15,17
				20080	FC8T9/D/RS	12	12000	6500	76	900	3,12,13,15,17
30	T9	9.00 - 9.50	4-Pin	20114	FC9T9/DCW/RS	6	10000	4100	82	2000	3,12,13,15,17
				20215	FC9T9/DSW/RP/1/6	6	10000	3000	82	1900	3,12,13,15,17
32	T9	11.5 - 12.0	4-Pin	20141	FC12T9/DCW/RS	6	15000	4100	80	1925	3,12,13,15,17
				20233	FC12T9/DSW/RP	6	15000	3000	70	2100	3,12,13,15,17
				20037	FC12T9/WW/RS	12	15000	3000	52	1950	3,12,13,15,17
				20142	FC12T9/CW/RS	12	15000	4200	60	1925	3,12,13,15,17
				20030	FC12T9/D/RS	12	15000	6500	76	1650	3,12,13,15,17
40	T9	15.6 - 16.0	4-Pin	20058	FC16T9/WW/RS	12	8000	3000	80	2500	3,12,13,15,17
				20172	FC16T9/DCW/RS	6	8000	4100	80	2750	3,12,13,15,17
				20059	FC16T9/CW/RS	12	8000	4200	60	2500	3,12,13,15,17

#### High Output (800mA) SUPERSAVER® Rapid Start Lamps

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life Hours per start 3hrs 12hrs	CCT (K)	CRI	Approx Lumens Initial (Mean) 25°C/77°F	Notes
95	T12	96	93.91	RecessedDC	25011	F96T12/WW/HO/SS	15	12000 18800	3000	52	7700 (6235)	☉*, 3,10, 12,13,17,36
					25024	F96T12/D35/HO/SS	15	12000 18800	3500	48	8350 (7515)	☉*, 3, 10,12,13,17,36
					25010	F96T12/CW/HO/SS	15	12000 18800	4200	60	8000 (6480)	☉*, 3,10, 12,13,17,36
					25001	F96T12/CW/HO/SS/ECO	15	12000 18800	4200	60	8000 (6480)	☉*, 3,10, 12,13,17,36

#### High Output (800mA) Rapid Start Lamps for Cold Temperature Operation

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life 3 Hours per start	CCT (K)	CRI	Approx Lumens Initial (Mean) 25°C/77°F	Notes
110	T12	96	93.91	RecessedDC	25129	F96T12/CW/HO/CT/ECO	15	12000	4200	60	8600 (6965)	☉, 3,12, 13,17,25,36
					25134	F96T12/CW/HO/COLDTEMP	15	12000	4200	60	8600 (6965)	☉, 3,12, 13,17,25
					25135	F96T12/D/HO/COLDTEMP	15	12000	6500	76	7600 (6155)	☉, 3,12, 13,17,25

\*means this bulb meets Federal minimum efficiency standards