



Ring Terminal
T&B Catalog Number:

RC363M
78621086294
Active

UPC Number:
Status:
Description:

Insulated Nylon Ring Terminal For Wire Range 12-10 Stud Size #10, Yellow, Military Specified (MIL-SPEC MS25036-112), Mylar Tape

WEB_USE

US Cutsheet PDF Catalog Link <http://www-public.tnb.com/contractor/docs/stakon.pdf>

Features

Self-insulated with high dielectric-strength nylon sleeves. An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.

Standards

UL, CSA

Application

Wiring terminations or connections for applications such as wiring harness, panelboard, telecommunications, and automotive.

General

Insulation Type	Insulated Nylon
Terminal Series	RC
Material	Copper
Finish	Electro -Tin Plated
Color	Yellow
Wire Range	12-10
Stud Size	#10

Dimension Information

Maximum Insulation (inches)	.210
Stock Thickness	.04
A (inches)	1.00
B (inches)	.37
C (inches)	.27
M (inches)	.81

Specifications

Temperature Rating	105°C
Voltage Rating	600V
Flammability Rating	UL 94 V-2
MIL Specification	MS-25036-112

Tooling

Tool Charts	Available on Website
Application Tools	WT2000, WT112M, WT145C, ERG4001, ERG4003, WT145A
Recommended Tool	12050

Packaging

T&B Order Multiple	500
T&B Inner Pack	500

Package in Units	2500
Package Type	Mylar Tape
T&B Sold in UOM	Each
T&B Weight Per UOM	8.75 lbs. per 1000
Alternate Package Qty	RC10-10

Application Support

Overview	Available on Website
Wire Guide Tables	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com