

## Double Ended Halogen Lamps

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
<b>Q300T3/CL/130V</b>	15166	300	130	R7s	C-8	4800	4.69/119.1	0.40/10.0	2,000
<b>Q300T3/CL/220V</b>	15168	300	220	R7s	C-8	4500	4.69/119.1	0.40/10.0	2,000
<b>Q300T3/CL/240V</b>	00196	300	240	R7s	C-8	4500	4.69/119.1	0.40/10.0	2,000
<b>Q500T3/CL/120V</b>	15170	500	120	R7s	C-8	10000	4.69/119.1	0.40/10.0	2,000
<b>Q500T3/CL/130V</b>	15172	500	130	R7s	C-8	9500	4.69/119.1	0.40/10.0	2,000
<b>Q500T3/CL/220V</b>	15174	500	220	R7s	C-8	9000	4.69/119.1	0.40/10.0	2,000
<b>Q500T3/CL/240V</b>	15176	500	240	R7s	C-8	9000	4.69/119.1	0.40/10.0	2,000
<b>Q750T3/CL/120V</b>	49568	750	120	R7s	C-8	15000	7.50/190.5	0.40/10.0	2,000
<b>Q750T3/CL/240V</b>	15180	750	240	R7s	C-8	16500	7.50/190.5	0.40/10.0	2,000
<b>Q1000T3/CL/120V</b>	49569	1000	120	R7s	C-8	22000	10.06/255.6	0.40/10.0	2,000
<b>Q1000T3/CL/220V</b>	15182	1000	220	R7s	C-8	21000	10.06/255.6	0.40/10.0	2,000
<b>Q1000T3/CL/240V</b>	15184	1000	240	R7s	C-8	21000	10.06/255.6	0.40/10.0	2,000
<b>Q1000T3/CL/277V</b>	15186	1000	277	R7s	C-8	22000	10.06/255.6	0.40/10.0	2,000
<b>Q1500T3/CL/120V</b>	49570	1500	120	R7s	CC-8	33000	10.06/255.6	0.40/10.0	2,000
<b>Q1500T3/CL/208V</b>	15188	1500	208	R7s	C-8	32000	10.06/255.6	0.40/10.0	2,000
<b>Q1500T3/CL/220V</b>	15190	1500	220	R7s	CC-8	32000	10.06/255.6	0.40/10.0	2,000
<b>Q1500T3/CL/240V</b>	15192	1500	240	R7s	CC-8	32000	10.06/255.6	0.40/10.0	2,000
<b>Q1500T3/CL/277V</b>	15194	1500	277	R7s	CC-8	34000	10.06/255.6	0.40/10.0	2,000

## Double Ended Short Halogen Lamps

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
<b>Q100W/S120V</b>	15200	100	120	R7s	C-8	1300	3.15/80.0	0.315/8.0	2,000
<b>Q100W/S130V</b>	15202	100	130	R7s	C-8	1300	3.15/80.0	0.315/8.0	2,000
<b>Q150W/S120V</b>	15206	150	120	R7s	C-8	2200	3.15/80.0	0.344/8.74	2,000
<b>Q150W/S130V</b>	15208	150	130	R7s	C-8	2200	3.15/80.0	0.344/8.74	2,000
<b>Q200W/S120V</b>	15211	200	120	R7s	C-8	3000	3.15/80.0	0.344/8.74	2,000
<b>Q200W/S130V</b>	15213	200	130	R7s	C-8	3000	3.15/80.0	0.344/8.74	2,000
<b>Q200W/S220V</b>	15209	200	220	R7s	CC-8	3000	3.15/80.0	0.344/8.74	2,000
<b>Q250W/S120V</b>	49571	250	120	R7s	CC-8	3500	3.15/80.0	0.360/9.13	2,000
<b>Q300W/S120V</b>	00019	300	120	R7s	CC-8	4100	3.15/80.0	0.360/9.13	2,000
<b>Q300W/S130V</b>	15216	300	130	R7s	CC-8	4100	3.15/80.0	0.360/9.13	2,000
<b>Q400W/S130V</b>	15221	400	130	R7s	C-8	5500	3.15/80.0	0.406/10.32	2,000

## G4 Base 2-pin Halogen Lamps

Item	Order Code	Watts	Volts	Base	Filament	Lumens	MOL in/mm	MOD in/mm	Life
<b>JC12V5W-FR</b>	81120	5	12	G4	C-6	60	1.38/35.0	0.36/9.0	2,000
<b>JCD12V5WH20</b>	15005	5	12	G4	C-6	60	1.22/31.0	0.32/8.2	2,000
<b>JCD12V10WH20</b>	15007	10	12	G4	C-6	150	1.22/31.0	0.36/9.0	2,000
<b>JCD6V10WH20</b>	15001	10	6	G4	C-6	150	1.22/31.0	0.36/9.0	2,000
<b>JC12V20W</b>	03510	20	12	G4	C-6	350	1.38/35.0	0.36/9.0	50
<b>JCD12V20WH20</b>	15009	20	12	G4	C-6	300	1.22/31.0	0.36/9.0	2,000
<b>JCD24V20WH20</b>	15011	20	24	G4	CC-6	280	1.22/31.0	0.32/8.2	2,000
<b>JCD6V20WH20</b>	15003	20	6	G4	C-6	300	1.22/31.0	0.36/9.0	2,000

>>Continued on page 35



Double Ended Short



G4 Base 2-Pin