

Non-NEMA Twist-Lock® Devices  
10A, 250V/15A, 125V, 3 Pole, 3 Wire  
Non-Grounding  
Insulgrip® Connector



Features

- Individually molded face for each blade configuration keeps debris out of plug interior
- Ribbed nylon housing is impact and chemical resistant
- Roomy wiring chamber provides ample space for wiring

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Black phenolic.	.296"-.625" (7.5-15.9)	783585237626	HBL7555



Specifications

Housing	Phenolic
Contacts	Copper alloy
Terminal Screws	#5-40 Brass
Clamp Plate	Zinc plated steel
Cord Clamps/Screws	Zinc plated steel
Assembly Screws	Nickel plated brass

Accessories

Plug	HBL7567C
Stainless Steel Flanged Inlet	HBL7556

Resources

eCatalog
----------

Performance

<b>Electrical</b>	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum
<b>Mechanical</b>	
Terminal Accommodation	#18 AWG - #10 AWG stranded copper wire only.
Terminal Identification	Terminals identified in accordance with UL 498
<b>Environmental</b>	
Flammability	HB or better per UL94/CSA 22.2 No.0.17
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)

