



# Steel City®


## Utility Boxes and Accessories



58351-1/2




58351-B-1/4  
"B" bracket  
recessed 1/4"




58361-1/2




58361-3/4




58361-V-1/2  
"CV" bracket  
recessed 1/2"




58371-1/2




58371-3/4




58371-T-1/2  
"T" bracket  
recessed 5/8"



58371-V-1/2  
"CV" bracket  
recessed 1/2"



59361-1/2




59361-3/4



58-C-1




58-C-4



58-C-5



58-C-6




58-C-7



58-C-11



58-C-16



58-C-30

### 4" x 2 1/8" Utility Boxes

| Cat.<br>No.                                        | Brkts. | Knockouts           |                    |                   | Std.<br>Ctn. |
|----------------------------------------------------|--------|---------------------|--------------------|-------------------|--------------|
|                                                    |        | Ea. Side<br>Conduit | Ea. End<br>Conduit | Bottom<br>Conduit |              |
| 1½" deep—with conduit KOs—10.3 cubic inch capacity |        |                     |                    |                   |              |
| 58351-1/2*                                         | —      | 3—½"                | 1—½"               | 2—½"              | 50           |
| 58351-B-1/4                                        | B      | 3—½"                | 1—½"               | 2—½"              | 25           |
| 1⅞" deep—with conduit KOs—13.0 cubic inch capacity |        |                     |                    |                   |              |
| 58361-1/2*                                         | —      | 3—½"                | 1—½"               | 2—½"              | 50           |
| 58361-3/4                                          | —      | 2—¾"                | 1—¾"               | 2—¾"              | 50           |
| 58361-V-1/2*                                       | CV     | 3—½"                | 1—½"               | 2—½"              | 50           |
| 2⅛" deep—with conduit KOs—14.5 cubic inch capacity |        |                     |                    |                   |              |
| 58371-1/2*                                         | —      | 3—½"                | 1—½"               | 2—½"              | 50           |
| 58371-3/4                                          | —      | 2—¾"                | 1—¾"               | 2—¾"              | 50           |
| 58371-T-1/2*                                       | T      | 3—½"                | 1—½"               | 2—½"              | 25           |
| 58371-V-1/2-25*                                    | CV     | 3—½"                | 1—½"               | 2—½"              | 25           |

\* Factory provided raised ground screw location.

### 4" x 2 1/8" Utility Box Extension Rings

1 1/8" deep—with conduit KOs—13.0 cubic inch capacity

| Cat. No.  | Knockouts        |                 | Std. Ctn. |
|-----------|------------------|-----------------|-----------|
|           | Ea. Side Conduit | Ea. End Conduit |           |
| 59361-1/2 | 3—1/2"           | 1—1/2"          | 50        |
| 59361-3/4 | 2—3/4"           | 1—3/4"          | 25        |

### 4" x 2 1/8" Utility Box Covers

Raised 1/4"

| Cat. No. | Dia. Hole (in.) | Description                                   | Std. Ctn. |
|----------|-----------------|-----------------------------------------------|-----------|
| 58-C-1   | —               | Blank                                         | 100       |
| 58-C-4   | 1 1/2"          | For 4-wire twist-lock single flush receptacle | 25        |
| 58-C-5   | 1 3/32"         | For single receptacle                         | 25        |
| 58-C-6   | —               | With 1/2" KO                                  | 25        |
| 58-C-7   | —               | For duplex flush receptacle                   | 100       |
| 58-C-11  | —               | With 1/2" bushed hole                         | 25        |
| 58-C-16  | —               | For single GFCI receptacle                    | 25        |
| 58-C-30  | —               | For one toggle switch                         | 100       |

Captivated screws

**Table 370-16(a). Metal Boxes**

| Box Dimension, (in.)<br>Trade Size or Type          | Min.<br>Cu. In.<br>Cap. | Maximum Number of Conductors |           |           |           |           |          |          |
|-----------------------------------------------------|-------------------------|------------------------------|-----------|-----------|-----------|-----------|----------|----------|
|                                                     |                         | No.<br>18                    | No.<br>16 | No.<br>14 | No.<br>12 | No.<br>10 | No.<br>8 | No.<br>6 |
| 4 x 1½ Round or Octagonal                           | 12.5                    | 8                            | 7         | 6         | 5         | 5         | 4        | 2        |
| 4 x 1½ Round or Octagonal                           | 15.5                    | 10                           | 8         | 7         | 6         | 6         | 5        | 3        |
| 4 x 2½ Round or Octagonal                           | 21.5                    | 14                           | 12        | 10        | 9         | 8         | 7        | 4        |
| 4 x 1½ Square                                       | 18.0                    | 12                           | 10        | 9         | 8         | 7         | 6        | 3        |
| 4 x 1½ Square                                       | 21.0                    | 14                           | 12        | 10        | 9         | 8         | 7        | 4        |
| 4 x 2½ Square                                       | 30.3                    | 20                           | 17        | 15        | 13        | 12        | 10       | 6        |
| 4½ x 1½ Square                                      | 25.5                    | 17                           | 14        | 12        | 11        | 10        | 8        | 5        |
| 4½ x 1½ Square                                      | 29.5                    | 19                           | 16        | 14        | 13        | 11        | 9        | 5        |
| 4½ x 2½ Square                                      | 42.0                    | 28                           | 24        | 21        | 18        | 16        | 14       | 8        |
| 3 x 2 x 1½ Device                                   | 7.5                     | 5                            | 4         | 3         | 3         | 3         | 2        | 1        |
| 3 x 2 x 2 Device                                    | 10.0                    | 6                            | 5         | 5         | 4         | 4         | 3        | 2        |
| 3 x 2 x 2½ Device                                   | 10.5                    | 7                            | 6         | 5         | 4         | 4         | 3        | 2        |
| 3 x 2 x 2½ Device                                   | 12.5                    | 8                            | 7         | 6         | 5         | 5         | 4        | 2        |
| 3 x 2 x 2½ Device                                   | 14.0                    | 9                            | 8         | 7         | 6         | 5         | 4        | 2        |
| 3 x 2 x 3½ Device                                   | 18.0                    | 12                           | 10        | 9         | 8         | 7         | 6        | 3        |
| 4 x 2½ x 1½ Device                                  | 10.3                    | 6                            | 5         | 5         | 4         | 4         | 3        | 2        |
| 4 x 2½ x 1½ Device                                  | 13.0                    | 8                            | 7         | 6         | 5         | 5         | 4        | 2        |
| 4 x 2½ x 2½ Device                                  | 14.5                    | 9                            | 8         | 7         | 6         | 5         | 4        | 2        |
| 3½ x 2 x 2½ Masonry Box/Gang                        | 14.0                    | 9                            | 8         | 7         | 6         | 5         | 4        | 2        |
| 3½ x 2 x 3½ Masonry Box/Gang                        | 21.0                    | 14                           | 12        | 10        | 9         | 8         | 7        | 4        |
| FS—Minimum Internal Depth<br>1½ Single Cover/Gang   | 13.5                    | 9                            | 7         | 6         | 6         | 5         | 4        | 2        |
| FD—Minimum Internal Depth<br>2½ Single Cover/Gang   | 18.0                    | 12                           | 10        | 9         | 8         | 7         | 6        | 3        |
| FS—Minimum Internal Depth<br>1½ Multiple Cover/Gang | 18.0                    | 12                           | 10        | 9         | 8         | 7         | 6        | 3        |
| FD—Minimum Internal Depth<br>2½ Multiple Cover/Gang | 24.0                    | 16                           | 13        | 12        | 10        | 9         | 8        | 4        |

Underwriters Laboratories Inc. File Number: E2969 (U.L. 514A)

Canadian Standards Association File Number: LR 12798

Federal Manufacture Number: 56501 (Cage Code)

Products Designed To Meet Federal Specification Number: W-J-800

Verification of file numbers and compliance with federal specifications for individual items available upon request.

Box and Cover Material and Plating Specification: .062" minimum thickness, Hot Rolled, Pre galvanized steel, minimum spangle.

ASTM G-90-U, AISI C-1008

Bracket Material: All brackets except MS style; 16 gauge (.060") Hot Rolled, Pre galvanized Steel AISI C-1008, G-90-U. MS Style bracket; 20 gauge (.036") Cold Rolled Spring Steel AISI C-1055, Heat Treated to R. 35 Zinc Plated .0005 thick.

Patent Number 5,031,789 - Standoff for Outlet Boxes - SS-1 Patent Number 5,004,199 - Metal Stud Bracket - Type MS - Eccentric Knockouts - Type Eko