



BT56

METALARC® STANDARD Probe Start Lamps (Cont'd)

PROBE START METAL HALIDE LAMPS

See product information bulletin (HID033) for product details

Watts	Bulb	Base	Product Number	Ordering Abbreviation	ANSI Code/ Fixture Req.	Pkg Qty	Lamp Finish	Operating Position	Avg Rated Life (hrs)	Approx Lumens Initial (Mean)	CRI	CCT (K)	Lamp Efficacy (LPW)
1000	BT37	E39Mogul	64469	M1000/U/BT37	M47/E	6	Clear	Universal	15000V 9000H	110000V (96000V) 107800H (86300H)	65	3800	110 108
	BT56	E39Mogul	64468	M1000/U	M47/S	6	Clear	Universal	18000V 12000H	110000V (86000V) 107800H (86000H)	65	4000	110 108
1000	BT56	E39Mogul	64470	M1000/C/U	M47/S	6	Coated	Universal	18000V 12000H	107000V (80000V) 101600H (80700H)	70	3400	107 102
1500	BT56	E39Mogul	64431	M1500/BU-HOR	M48/E	6	Clear	BU-HOR	3000 ²	170000V (140000V) 153000H (127400H)	70	4000	113 102

² Published rated life based on 5 hours per start. Life rating will increase to 6,000 hours if operated for at least 10 hours per start in the base up position. Lumens will be lower for operating positions other than base up. See lumen tilt factor curve in the Metal Halide Specification Guide (HID017).

H
I
D