

Product availability : Stock - Normally stocked in distribution facility



Price* : 58.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	15 A
System Voltage	120/240 V AC
Mounting mode	Plug-in
Poles description	1P
Circuit breaker type	Tandem
Circuit breaker application	HACR rated
Electrical connection	Pressure plate
Accessory / separate part type	None

Complementary

Short-circuit current	10 kA
Number of spaces required	1
AWG gauge	AWG 12...AWG 8 (aluminium) AWG 14...AWG 8 (copper)

Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00004 - QO,QOT 10-30A 1P;10-60A 2P
Discount Schedule	DE2A
GTIN	00785901418009
Nbr. of units in pkg.	10

Package weight(Lbs)	0.32000000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------