



BDBMHC262/03, 3-Pole Power Distribution Block

By Burndy
 Catalog # [BDBMHC262/03](#)

Terminal block covers, AWG 14 - 2/0 (Run), AWG 14 - 2 (Tap), Power Distribution Block, Amp rating:350



Features

- VERSIPOLE Configurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Application

Industrial control feeder, HVAC system and wire ways

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - AL Str Run	<ul style="list-style-type: none"> • 12 • 10 • 8 • 6 • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - AL Str Run Range	12-2/0
Conductor - AL Str Tap	<ul style="list-style-type: none"> • 12 • 10 • 8 • 6 • 4 • 3 • 2
Conductor - AL Str Tap Range	12-2
Conductor - Copper Str Run	<ul style="list-style-type: none"> • 14 • 12

	<ul style="list-style-type: none"> • 10 • 9 • 8 • 7 • 6 • 5 • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - Copper Str Run Range	14-2/0
Conductor - Copper Str Tap	<ul style="list-style-type: none"> • 14 • 12 • 10 • 9 • 8 • 7 • 6 • 5 • 4 • 3 • 2
Conductor - Copper Str Tap Range	14-2
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Run • CU C Str-Run • AL C Str-Tap • CU C Str-Tap
Number Of Poles	3
Current	
Rating - Minimum Voltage	600
Amperage Rating	350 A
Dimensions	
Package Length	13.000 in
Package Width	5.450 in
Package Weight	3.190 lb.
Dimension - L Length Overall mm	127 mm
Dimension - Height inch	3.25 in
Package Height	3.550 in
Dimension - Height mm	82.6 mm

Width	3.88 in
Dimension - Width inch	5.28 in
Dimension - Width mm	134 mm
Length	5.28 in
Dimension - Length Overall inch	5.00 in
Height	3.25 in
Dimensions	5.28 in x 3.88 in x 3.25 in

General

Trade Name	VERSIPOLE™
Insulation	Y
Sub Brand	VERSI-POLE
Plated	Y
Type	BDB
UPC 12 Digit	781810646045

UPC 14 Digit GTIN	00781810646045
Material	Aluminum
Plating Type	Tin
UPC	781810646045

Logistics

Minimum Pack Quantity	1
Carton Quantity	6
Pallet Quantity	288

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand