

Xitanium LED Driver Outdoor Dimmable (US)

Xitanium 150W 0.7A 0-10V INTELLIVOLT

Xitanium Outdoor LED Drivers are available in wattages from 40W to 150W for hard-wire integration into outdoor luminaires for the most rugged applications. These drivers operate to specification under wide temperature and electrical ranges to ensure reliability. 1-10V dimming enables luminaires to be easily connected to a wide variety of sensors and control systems to facilitate dimming, thus maximizing energy savings.

Benefits

· Operating and Electrical

Input frequency 50-60 Hz 20 % Total harmonic distortion IEC (max.) 90 % Maximum efficiency Power factor 100% 0.9 load (min.) Output current 700 mA (nom.) 5 % Output current tolerance (max.) Output current -5 % tolerance (min.) 120-277 V Input voltage (AC) 1400 mA Input current (max.) Input power (nom.) 165 W 150 W Output power (nom.) Output voltage 60-210 V

Wiring

Control wire length
Output wire length
Primary fusing
Secondary fusing
Input wire gauge
Control wire gauge
Output wire gauge
18
Output wire gauge
254.0 mm
Fused
None Required
18
0utput wire gauge
18

Temperature

T-Case maximum 80 °C (max.)

· Controls and Dimming

Control interface 0-10 V Dimming range 100-10 %

· Approval and Application

Overheating Protected protection Self-limited Short-circuit protection Over power Protected protection Protected Open circuit protection EMI standard FCC Title 47 Part15 Class A Environmental UL Damp & Dry standard RoHS compliance Approval marks UL certificate

CSA certificate

• Product Data


Output insulation

871016319630500 Full product code Order product name Xitanium 150W 0.7A 0-10V INTELLIVOLT EAN/UPC – product 781087070192 Order code 913710844102 Numerator quantity per pack Numerator - packs per outer box 913710844102 Material no. (12NC) Net weight (piece) 1.257 kg



Xitanium LED Driver Outdoor Dimmable (US)


Dimensional drawing



Xitanium LED drivers outdoor (Dimmable) F-can

Xitanium 150W 0.70A DIM INTELLIVOLT

Product	B2	C1	C2	A1	A2	A3	B1
LEDINTA0700C210DOM	42,9 mm	40.1 mm	37.7 mm	240.5 mm	226.3 mm	211.1 mm	59.2 mm





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.