







1492-JD3					1492-JD4				1492-JT3M																			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block. 																												
Specifications					Two-level, two-circuit feed-through terminal block				Two-level, two-circuit feed-through terminal block				Three-level, three-circuit terminal block with ground point															
Certifications						CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC													
Voltage Rating					600V AC/DC		300V AC/DC		400V AC/DC		275V AC/DC		600V AC/DC		300V AC/DC		400V AC/DC											
Maximum Current					20 A		10 A		24 A		21 A		35 A		30 A		32 A		28 A		10 A		24 A					
Wire Range (Rated Cross Section)					#22...12 AWG		#26...12 AWG		2.5 mm ²		2.5 mm ² (20...14 AWG)		#26...10 AWG		0.5...4 mm ²		4 mm ² (20...12 AWG)		#22...12 AWG		#26...10 AWG		0.5...2.5 mm ²					
Wire Strip Length					0.39 in. (10 mm)								0.315 in. (8 mm)								0.28 in. (7 mm)							
Recommended Tightening Torque					4.5...7.1 lb•in (0.5...0.8 N•m)								4.5 lb•in (0.5 N•m)								4.4 lb•in (0.5 N•m)							
Density					59 pcs/ft (196 pcs/m)								49 pcs/ft (163 pcs/m)								49 pcs/ft (163 pcs/m)							
Housing Temperature Range					-58...+248 °F (-50...+120 °C)								-58...+248 °F (-50...+120 °C)								-58...+248 °F (-50...+120 °C)							

1492-J2Q					1492-J3TW				1492-J4TW																			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block. 																												
Specifications					Feed-through terminal block with 2 connection points on each side				Feed-through terminal block with 3 connection points, 2 on one side				Feed-through terminal block with 3 connection points, 2 on one side															
Certifications						CSA	IEC		CSA	IEC	ATEX		CSA	IEC														
Voltage Rating					300V AC/DC		800V AC/DC		300V AC/DC		800V AC/DC		550V AC/DC		600V AC/DC		500V AC/DC											
Maximum Current					25 A		10 A		17.5 A		—		30 A		—		32 A											
Maximum Current					Single Side		—		10 A		15 A		17.5 A		15 A		—											
Maximum Current					Twin Side		—		20 A		24 A		21 A		—		—											
Wire Range (Rated Cross Section)					Single Side		#22...12 AWG		#26...12 AWG		1.5 mm ²		#22...12 AWG		26...12 AWG		2.5 mm ² (#20...14 AWG)		#30...10 AWG		4 mm ²							
Wire Range (Rated Cross Section)					Twin Side		—		#22...12 AWG		26...12 AWG		1.5 mm ²		1.5 mm ² (#20...16 AWG)													
Wire Strip Length					0.28 in. (7 mm)								Single Side: 0.39 in. (10 mm) Twin Side: 0.26 in. (7 mm)								0.39 in. (10 mm)							
Recommended Tightening Torque					4.5 lb•in (0.5 N•m)								Single Side: 7.0 lb•in (0.8 N•m) Twin Side: 4.5 lb•in (0.5 N•m)								6.2 lb•in (0.7 N•m)							
Density					59 pcs/ft (196 pcs/m)								59 pcs/ft (196 pcs/m)								59 pcs/ft (196 pcs/m)							
Housing Temperature Range					-58...+248 °F (-50...+120 °C)								-58...+248 °F (-50...+120 °C)								-58...+248 °F (-50...+120 °C)							

Terminal Block Specifications

Cat. No.	Wire Size [AWG]																		
	#30	#28	#26	#24	#22	#20	#18	#16	#14	#12	#10	#8	#6	#4	#2	#1	1/0	2/0	3/0
	(0.05)	(0.08)	(0.13)	(0.21)	(0.33)	(0.5)	(0.75)	(1.5)	(2.5)	(4)	(6)	(10)	(16)	(25)	(35)	(40)	(50)	(70)	(80)
Number of the Same Size Wires Per Terminal																			
1492-CA1	—	—	—	—	4	4	4	3	2	2	1	1	—	—	—	—	—	—	—
1492-CAM1	—	—	—	—	4	4	4	3	2	2	1	1	—	—	—	—	—	—	—
1492-H4	1	1	1	1	4	4	3	2	2	1	1	—	—	—	—	—	—	—	—
1492-H5	1	1	1	1	4	4	3	2	2	1	1	—	—	—	—	—	—	—	—
1492-H6	1	1	1	1	4	4	3	2	2	1	1	—	—	—	—	—	—	—	—
1492-H7	1	1	1	1	4	4	3	2	2	1	1	—	—	—	—	—	—	—	—
1492-HM3	—	—	—	—	4	4	4	3	2	2	1	1	—	—	—	—	—	—	—
1492-J10	—	—	—	—	4	4	4	4	3	2	1	1	1	—	—	—	—	—	—
1492-J16	—	—	—	—	—	—	1	4	4	3	2	1	1	1	—	—	—	—	—
1492-J2Q	—	—	4	4	4	3	1	1	1	—	—	—	—	—	—	—	—	—	—
1492-J3	4	4	4	4	4	4	3	3	2	1	—	—	—	—	—	—	—	—	—
1492-J35	—	—	—	—	—	—	—	—	3	3	3	2	2	1	1	1	1	—	—
1492-J3F	4	4	4	4	4	4	3	3	2	1	—	—	—	—	—	—	—	—	—
1492-J3P	4	4	4	4	3	3	3	3	2	1	—	—	—	—	—	—	—	—	—
1492-J3TW (single side)	4	4	4	4	4	4	3	3	2	1	—	—	—	—	—	—	—	—	—
1492-J3TW (twin side)	—	—	4	4	4	3	1	1	1	—	—	—	—	—	—	—	—	—	—
1492-J4	—	—	—	—	4	4	3	3	2	1	1	—	—	—	—	—	—	—	—
1492-J4CTB	—	—	1	1	4	4	3	3	2	1	1	—	—	—	—	—	—	—	—
1492-J4Q	1	1	1	1	1	4	3	3	2	1	1	—	—	—	—	—	—	—	—
1492-J4TW	1	1	1	1	1	4	3	3	2	1	1	—	—	—	—	—	—	—	—
1492-J50	—	—	—	—	—	—	—	—	—	—	1	2	2	1	1	1	1	—	—
1492-J6	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB2	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB224	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB248	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB2120	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB2250	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB1	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB124	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB148	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB1120	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J6FB1250	—	—	—	—	4	4	3	3	3	2	1	1	—	—	—	—	—	—	—
1492-J70	—	—	—	—	—	—	—	—	5	5	5	2	2	2	1	1	1	1	1