

Applications


- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features


- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- Screw machined bodies (straight through 1") and precision threaded malleable iron castings mate with other components perfectly without strain or distortion
- All components are reusable — RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation

Compliances

-  - Standard 514B
-  - C22.2 #18



STRAIGHT-INSULATED
STEEL/MALLEABLE IRON




STRAIGHT-UNINSULATED
STEEL/MALLEABLE IRON

ORDERING INFORMATION - DIMENSIONS

STRAIGHT - INSULATED AND UNINSULATED - STEEL/MALLEABLE IRON					
INSULATED IRON CATALOG NUMBER	UNINSULATED IRON CATALOG NUMBER	TRADE SIZE	UNIT CTN. QTY.	SHIP CTN. QTY.	UPC BAR CODE
3511*	—	3/8"	25	100	—
—	3401*	3/8"	50	200	—
3512	3402	1/2"	50	200	—
3512-8	3402-8	1/2"	1	15	
3513	3403	3/4"	25	100	—
3513-8	3403-8	3/4"	1	10	
3514	3404	1"	—	10	—
3514-8	3404-8	1"	1	5	
3515	3505	1-1/4"	—	10	—
3516	3406	1-1/2"	—	5	—
3518	3408	2"	—	5	—
3520	3410	2-1/2"	—	1	—
3522	3412	3"	—	1	—
3524	3414	3-1/2"	—	1	—
3526	3416	4"	—	1	—

*1/2" Trade size hub

DIMENSIONS				
TRADE SIZE	A	B	THREAD SPEC.	C
3/8"	1-1/16"	19/32"	1/2-14 NPT	1-7/16"
1/2"	1-3/16"	19/32"	1/2-14 NPT	1-7/16"
3/4"	1-29/64"	19/32"	3/4-14 NPT	1-9/16"
1"	1-23/32"	21/32"	1-11-1/2 NPT	1-11/16"
1-1/4"	2-3/16"	5/8"	1-1/4-11-1/2 NPT	2-1/32"
1-1/2"	2-1/2"	5/8"	1-1/2-11-1/2 NPT	2-7/32"
2"	3"	21/32"	2-11-1/2 NPT	2-9/32"
2-1/2"	3-5/8"	1"	2-1/2-8 NPT	3-1/2"
3"	4-5/16"	1"	3-8 NPT	3-3/4"
3-1/2"	4-13/16"	1"	3-1/2-8 NPT	3-3/4"
4"	5-5/16"	1"	4-8 NPT	3-3/4"



A = Nut Flats
B = Thread length and thread spec.
C = Overall length