

Selector switch, metal Spring return left & right Long lever, no insert
1NO-1NC left, right 3 Position, C Cam Complete device white insert
Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Enclosure

| | |
|--|----|
| Number of command points | 1 |
| Delivery state | No |
| <ul style="list-style-type: none"> • as a kit | |

Actuator

| | |
|--|---------|
| Material of the actuating element | plastic |
| Number of contact modules | 1 |
| Type of unlocking device | without |
| Number of switching positions | 3 |

Front ring

| | |
|-------------------------------------|----------|
| Product component front ring | Yes |
| Design of the front ring | standard |
| Material of the front ring | metal |

General technical data

| | |
|--|--------------|
| Product function | |
| <ul style="list-style-type: none"> • positive opening | Yes |
| Product component | |
| <ul style="list-style-type: none"> • Light source | No |
| Insulation voltage | |
| <ul style="list-style-type: none"> • rated value | 600 V |
| Protection class IP | |
| <ul style="list-style-type: none"> • of the terminal | IP66 IP20 |
| Operating frequency maximum | 600 1/h |
| Thermal current | 10 A |

Auxiliary circuit

| | |
|--|--------------|
| Number of NC contacts for auxiliary contacts | 1 |
| Number of NO contacts for auxiliary contacts | 1 |
| Operating current at AC-15 | |
| <ul style="list-style-type: none"> • at 110 V rated value • at 500 V rated value | 60 A 12 A |

Connections/ Terminals

| | |
|---|----------------------|
| Type of electrical connection | screw-type terminals |
| Tightening torque of the screws in the bracket | 20 N·m |

| | |
|---|----------|
| Tightening torque [lbf·in] | |
| <ul style="list-style-type: none"> with screw-type terminals | 8 lbf·in |

Ambient conditions

| | |
|--|----------------|
| Ambient temperature | |
| <ul style="list-style-type: none"> during operation | -35 ... +70 °C |
| <ul style="list-style-type: none"> during storage | -40 ... +85 °C |

Installation/ mounting/ dimensions

| | |
|--|-------|
| Shape of the installation opening | round |
|--|-------|

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2CDBA1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2CDBA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2CDBA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2CDBA1&lang=en

last modified: 11/13/2019