



Bulletin 100-C/104-C — IEC Contactors

- Compact sizes from 4...55 kW/5...75 Hp (9...97 A)
- AC and DC coil control
- Common accessories for all contactor sizes
- Front and side mounting of auxiliary contacts
- Electronic and pneumatic timing modules
- Space-saving coil-mounted control modules
- Reversible coil terminations (line or load side)
- All devices can be attached to 35 mm DIN mounting Rail
- Environmentally friendly materials

The Bulletin 100-C/104-C IEC contactor family, along with a wide range of common accessories and Bulletin 193 solid-state overload relays, provides the most compact and flexible starter component system available.

Your order must include: cat. no. of the contactor specified with coil voltage code and, if required, cat. no. of any accessories and/or replacement coils.

Table of Contents

Product Selection this page
 Accessories..... 2-142
 Approximate
 Dimensions..... 2-194

Standards Compliance

EN/IEC 60947-4-1, 60947-5-1
 IEC 60947 Type "2"
 Coordination
 CSA C22.2 No. 14
 UL 508
 Meets the material restrictions
 for European Directive
 2002/95/IEC-EU-RoHS

Certifications

CE Marked
 cULus Listed (File No. E3125;
 Guide NLDX, NLDX7)
 CCC

Product Selection

3-Pole AC- and DC-Operated Contactors

/e [A]		Ratings for Switching AC Motors — AC-2, AC-3, AC-4										Aux. Contacts		Cat. No.
		3-Phase kW (50 Hz)				Hp (60 Hz)								
AC-3	AC-1	230V	400V/415V	500V	690V	1-Phase		3-Phase						
						115V	230V	200V	230V	460V	575V			
9	32	3	4	4	4	1/2	1-1/2	2	2	5	7-1/2	1	0	 100-C09 
												0	1	 100-C09 
12	32	4	5.5	5.5	5.5	1/2	2	3	3	7-1/2	10	1	0	 100-C12 
												0	1	 100-C12 
16	32	5.5	7.5	7.5	7.5	1	3	5	5	10	15	1	0	 100-C16 
												0	1	 100-C16 
23	32	7.5	11	13	10	2	3	5	7-1/2	15	15	1	0	100-C23 
												0	1	100-C23 
30	65	10	15	15	15	2	5	7-1/2	10	20	25	0	0	100-C30 
												1	0	100-C30 
												0	1	100-C30 
37	65	11	18.5/20	20	18.5	3	5	10	10	25	30	0	0	100-C37 
												1	0	100-C37 
												0	1	100-C37 
43	85	13	22	25	22	3	7-1/2	10	15	30	30	0	0	100-C43 
												1	0	100-C43 
												0	1	100-C43 
60	100	18.5	32	37	32	5	10	15	20	40	50	0	0	100-C60 
												1	0	100-C60 
												0	1	100-C60 
72	100	22	40	45	40	5	15	20	25	50	60	0	0	100-C72 
												1	0	100-C72 
												0	1	100-C72 
85	100	25	45	55	45	7-1/2	15	25	30	60	60	0	0	100-C85 
												1	0	100-C85 
												0	1	100-C85 
97	130	30	55	55	55	10	15	30	30	75	75	0	0	100-C97 
												1	0	100-C97 
												0	1	100-C97 

‡ For screwless terminals, add an "R" after the letter "C" in the catalog number. Example: **Cat. No. 100-C09⊗10** becomes **Cat. No. 100-CR09⊗10**.

⊗ Coil voltage code and terminal position—see page 2-131



Allen-Bradley

www.ab.com/catalogs Preferred availability cat. nos. are **bold**.

Publication A117-CA001A-EN-P