



Actual

Catalog Number: GRNY-100-9-C
Product ID: 7TAG009750R0028
UPC Number: 72849411922
EAN Number: 05414363023616
Status: Active

Extruded Grommeting, Natural Nylon 6.6 for Temperatures up to 85 Degrees Celsius (185 F), Height of 5.58mm (0.220 Inches), Width of 5.33mm (0.21 Inches), Thickness 1.14mm (0.045 Inches), Width Maximum Panel Thickness of 2.54mm (1.05 Inches), 30.48m (100 Foot) Reel

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 - .250 inches thick and in a variety of stocked materials to cover a wide range of applications.

UNSPSC Specifications

UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Type	Grommeting
Special Features	Used to line panel edges and knockouts where the chafing of wires is a concern.
Color	Natural
Panel Thickness	0.100
Material	Nylon/Polyamide 6.6

ETIM Specifications

ETIM	EC000879 Feed through spout
For wall thickness	2.54-2.54mm
Total length	30480mm
Model	Open
Shrink technique	N
Angle model	N
Material	Plastic
Material quality	Polyamide
Surface protection	Untreated
Halogen free	Y
Colour	Natural colour
Gastight	N
Fire resistant	Y
Watertight	N

Packaging

Inner Quantity	1
Inner Dimensions (inches)	17x12x1.75
Outer Quantity	10
Outer Dimensions (inches)	18x12.5x12
Weight Uom	1.4 lbs. Each

Documents / Support Tools

Technical Data Sheet CA Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com