

# Weather-Resistant Commercial Grade Receptacles, White

WR20TRW



Weather-Resistant Commercial Grade Receptacles, 20 amp, 125 volts, White, WR20TRW

## features & benefits

- Auto-ground clip assures positive ground.
- WR marking on face as required by UL Standard.
- Zinc-plated steel mounting screws for greater ease of installation and removal in wet or damp locations.
- Strap tabs wrap around face to prevent strap from separating from face and back body.
- Tri-drive brass terminal screws. Internal screwpressure plate back and side wire capability. Two back wire holes for more wiring flexibility.
- Heavy-duty, brass strap for added strength and ground conductivity.
- UV-resistant nylon face for longer life under adverse environmental conditions.
- Two drive screws anchor strap to backbody and face where abrupt removal torque is strongest.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- .032 inch thick brass triple-wipe power contacts for lasting retention.

## specifications

### General Info

Color: white  
Type: Receptacles  
Features: Weather-Resistant

Number Of Poles: 2  
Number Of Wires: 3  
Special Features: Weather-Resistant,Tamper-Resistant  
Style: Duplex

### **Listing Agencies/Third Party Information**

CSA Listing Info: C22.2 No. 42  
CSA Standard: Yes  
UL Listing No: UL498  
UL Standard: Yes  
UN SPS C: 39121406

### **Dimensions**

Depth U S: 1.130"  
Height U S: 3.281"  
Width U S: 1.322"

### **Technical Information**

Amps: 20 Amp  
NEMA Configuration Number: 5-20R  
Volts: 125V  
Volts A C: 125  
Capacity: Duplex  
Grade Type: Commercial

### **Buy American Act Compliance**

Buy American Act Status: Trade Agreement Act Compliant