



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Transformers](#) > [Dry Type, Encapsulated, Enclosed](#)

Transformers, Dry Type, Encapsulated, Enclosed

Product #: 9T51B0108

Short Description: ENCLOSED SMALL POWER TRANSFORMERS

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Buck Boost
Phase	1
PriVoltage	120x240
SecVoltage	12/24
KVA	0.5 KVA
Coil Material	CU
TempRise	100 °C
ElecShield	N
SubType	BUCK BOOST
Frequency	60 Hz
UL	Yes
FrameSize	10225
cUL	Yes
CE	No
Width	6.88 in
Depth	4.88 in
Height	8.38 in
TempClass	180 °C
AmbTemp	40 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Sound	Std
GSA Compliance	Yes
GO Schedule	90B
List Price	\$209



[View Larger](#)

Publications/Resources

[9T51B0108](#)

Additional Resources for Buck Boost

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[Buy Log :8-55](#)

These GE transformers feature an encapsulated core and coil in a NEMA 3R non-ventilated weatherproof enclosure.

- UL Listed
- C-UL Listed
- Knockouts provided on back and bottom
- High grade silicon steel core
- Mounting holes on side for easy access
- Wiring compartment includes ground stud

