



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TC35321

Short Description: 30A 3P DBL THR SS N1 240V NONFUSE

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	Double Throw
Voltage	240 AC
Amperage	30 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 1 (Indoor)
Options	None
Height	15.78 in
Depth	5.17 in
Width	10.42 in
Weight	14.0 lb
Wire Range (Cu/Al)	14-8 CU;12-8 AL
240 Vac, NEC Std, 3-ph	2 hp
GSA Compliance	Yes
CSA Certified	No
UL Listed	Yes
GO Schedule	131B
List Price	\$482



[View Larger](#)

**Publications/Resources**

[TC35321](#)

**Additional Resources for Double Throw**

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[Installation and Instruction](#)

[Buy Log :2-20](#)

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Suitable for use as transfer equipment in standby systems in accordance with Article 702 of the National Electrical Code.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- 60/75°C conductor ratings.
- Full cover interlocks.