

Description: 16 AWG 4/C AUDACIOUS HTS. UL CL3R OR CMR C(UL)US FT4

Specifications: UL Standards 13 & 444; NEC Articles 725 & 800, CSA C22.2 NO. 214

#### Construction:

Conductor 16 AWG 65/34 Stranded  
Insulation OFBC  
Insulation Thickness PVC  
Insulation Colors 0.015" nom.  
Insulation Diameter Blk,Red,Wht,Grn  
Lay Length 0.086 nom.  
4.0" nom.

Jacket PVC  
Jacket Color Purple or White  
Jacket Thickness 0.035" nom.  
Outside Diameter 0.294" nom.

Legend (Ink Print) HONEYWELL AUDACIOUS OXYGEN FREE P/N 5474 4C16 E175106 (UL) CL3R OR CMR C(UL)US FT4 75C SUN RES (RoHS) W/O#XXXXXX-XXXXXX XXXXX FT - L C R LR RR RM# A B C D E F 1 2 3 4 5 6 7 8 9 (PAT PEND)

#### Properties

Temperature Rating -20 to 75 °C  
Operating Voltage 300 Volts max.  
Capacitance 22 pf/ft nom.  
Impedance 85 Ohms nom.  
DC Resistance 4.10 Ohms/M' at 20°C  
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 25.25 (FT4)