

Insulated Multi-Taps

These dual-rated blocks can be used with copper or aluminum cable.

Aluminum Multi-Tap Encapsulated Cable Blocks — One-Way Configuration

- Versatile design supports a wide range of cable sizes and number of outlets available in one-way configurations
- Clear PVC insulation enables safe and time-saving installation with no taping required
- Meets or exceeds ANSI C119.4 specifications



CAT. NO.	NO. OF OUTLETS	WIRE RANGE	SCREW SIZE	DIMENSIONS (IN.)		
				LENGTH	WIDTH	HEIGHT
Splices						
CSR 2/0	2	#14-2/0	3/8 Hex	2 3/4	7/8	1 1/8
CSR 250	2	#6-250		4 1/8	1 1/8	2 1/8
CSR 350	2	#6-350		4 3/4	1 3/8	2 1/2
CSR 500	2	2/0-500		6 1/2	1 3/8	2 1/8
Cable Blocks						
CSB 4-2 S	2	#4-#14	Slotted	1 1/8	1 3/8	1 1/8
CSB 4-3 S	3			1 1/16		
CSB 4-4 SAH*	4			2 1/16		
CSB 4-5 S	5			2 9/16		
CSB 4-6 S	6			3 1/16		
CSB 4-7 S	7			3 3/16		
CSB 4-8 SAH*	8			4 1/16		
CSB 2/0-2 S	2			2/0-#14		
CSB 2/0-3 S	3	2 3/8				
CSB 2/0-4 S	4	3 1/8				
CSB 2/0-5 S	5	3 3/8				
CSB 2/0-6 S	6	4 3/8				
CSB 2/0-7 S	7	5 3/8				
CSB 2/0-8 S	8	6 3/8				
CSB 250-2 S	2	250-#6	3/16 Hex		1 3/8	2 3/8
CSB 250-3 S	3			2 7/32		
CSB 250-4 S	4			3 13/16		
CSB 250-5 S	5			4 29/32		
CSB 250-6 S	6			5 3/4		
CSB 250-7 S	7			6 3/4		
CSB 250-8 S	8			7 5/64		
CSB 350-2 S	2			350-#10	3/16 Hex	
CSB 350-3 S	3	3 1/4				
CSB 350-4 S	4	4 1/4				
CSB 350-5 S	5	5 1/4				
CSB 350-6 S	6	6 1/4				
CSB 350-7 S	7	7 1/4				
CSB 350-8 S	8	8 1/4				
CSB 500-2 S	2	500-#6	3/16 Hex			2 7/8
CSB 500-3 S	3			4 1/8		
CSB 500-4 S	4			5 3/8		
CSB 500-5 S	5			6 3/8		
CSB 500-6 S	6			7 3/8		
CSB 500-7 S	7			9 1/8		
CSB 500-8 S	8			10 3/8		

* Not UL Listed, includes hex screw.