



T&B[®]

Rigid/IMC Conduit Fittings
T&B Catalog Number:

UPC Number: HTZ5
Status: 04226949580
Description: Active

1 1/2 in. Chase Zinc Conduit Hub with insulated throat. For use with Rigid/IMC Conduit.

Features

- Chase design provides maximum space for wiring in the box, locking nipple sits flush in the enclosure.
- Captive O-ring fits snugly in groove preventing loss and fumbling with parts.
- Knurled inner face of locking nipple provides 360 degrees of locking and bites through box wall to ensure grounding.
- Locking nipple has tightening lugs on two planes for easier assembly in hard to reach field conditions.
- Plastic insulated throat, precision cast and machined surfaces permit safer wire pulling.

Application

- Hubs provide raintight connections between junction boxes or between a junction box and conduit system while maintaining ground continuity.
- Suitable for use where the system is normally hosed down (NEMA 4) for cleaning.

General

Trade Size (inches) 1-1/2
 Material Die Cast Zinc
 Finish Aluminum Lacquer

Dimension Information

Dimension A (inches) 1 3/4
 Dimension B (inches) 2 5/8
 Dimension C (inches) 1/4
 Dimension D (inches) 1/4
 Dimension E (inches) 1 1/2 - 11 1/2
 Dimension F (inches) 60
 Dimension G (inches) 1 29/32
 Dimension H (inches) 2 13/64
 Dimension J (inches) 227

Specifications

3dmodel Available on Website

Packaging

Package in Units 10
 T&B Sold in UOM Each
 T&B Weight Per UOM 0.77 lbs. Each

Application Support

Product Brochure

Available on Website

Certifications



File Nbr:

E 28720

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com