



Polaris Connectors

UNINSULATED MULTI-CABLE CONNECTOR BLOCKS

PL SERIES



PL Series connectors are made from 6061-T6 aluminum alloy and are plated for corrosion resistance. They are stocked in one hole increments, up to 14 holes and are suitable for use on wire from #4 AWG to 750 MCM. Dual rated for use with copper and/or aluminum cables. Rated 600 V, 90°C. Not recommended for fine-stranded, flexible wire.

CATALOG NO.	UPC NO.	NO. OF PORTS	WIRE RANGE	(INCHES)			HEX SIZE	CARTON QTY.	WEIGHT LBS./EA
				LENGTH	HEIGHT	WIDTH			
PL 4-3	90001	3	4-14	1.30	.62	.50	Slotted	12	.04
PL 4-4	90002	4	4-14	1.73	.62	.50	Slotted	12	.05
PL 4-5	90003	5	4-14	2.15	.62	.50	Slotted	6	.06
PL 4-6	90004	6	4-14	2.57	.62	.50	Slotted	6	.08
PL 4-7	90005	7	4-14	2.99	.62	.50	Slotted	6	.09
PL 4-8	90006	8	4-14	3.41	.62	.50	Slotted	6	.10
PL 4-9	90007	9	4-14	3.84	.62	.50	Slotted	6	.11
PL 4-10	90008	10	4-14	4.26	.62	.50	Slotted	4	.12
PL 4-11	90009	11	4-14	4.68	.62	.50	Slotted	4	.14
PL 4-12	90010	12	4-14	5.10	.62	.50	Slotted	4	.15
PL 4-13	90011	13	4-14	5.52	.62	.50	Slotted	2	.16
PL 4-14	90012	14	4-14	5.95	.62	.50	Slotted	2	.17
PL 1/0-3	90101	3	1/0-14	2.01	.87	.62	3/16	12	.10
PL 1/0-4	90102	4	1/0-14	2.66	.87	.62	3/16	12	.14
PL 1/0-5	90103	5	1/0-14	3.31	.87	.62	3/16	6	.17
PL 1/0-6	90104	6	1/0-14	3.96	.87	.62	3/16	6	.20
PL 1/0-7	90105	7	1/0-14	4.61	.87	.62	3/16	6	.24
PL 1/0-8	90106	8	1/0-14	5.26	.87	.62	3/16	6	.27
PL 1/0-9	90107	9	1/0-14	5.91	.87	.62	3/16	6	.30
PL 1/0-10	90108	10	1/0-14	6.56	.87	.62	3/16	4	.34
PL 1/0-11	90109	11	1/0-14	7.21	.87	.62	3/16	4	.37
PL 1/0-12	90110	12	1/0-14	7.86	.87	.62	3/16	4	.40
PL 1/0-13	90111	13	1/0-14	8.51	.87	.62	3/16	2	.44
PL 1/0-14	90112	14	1/0-14	9.16	.87	.62	3/16	2	.47
PL 3/0-3	90201	3	3/0-6	2.37	.94	.69	1/4	6	.15
PL 3/0-4	90202	4	3/0-6	3.15	.94	.69	1/4	6	.19
PL 3/0-5	90203	5	3/0-6	3.93	.94	.69	1/4	6	.24
PL 3/0-6	90204	6	3/0-6	4.71	.94	.69	1/4	6	.29
PL 3/0-7	90205	7	3/0-6	5.49	.94	.69	1/4	6	.33
PL 3/0-8	90206	8	3/0-6	6.27	.94	.69	1/4	6	.38
PL 3/0-9	90207	9	3/0-6	7.05	.94	.69	1/4	4	.43
PL 3/0-10	90208	10	3/0-6	7.83	.94	.69	1/4	4	.47
PL 3/0-11	90209	11	3/0-6	8.61	.94	.69	1/4	3	.52
PL 3/0-12	90210	12	3/0-6	9.39	.94	.69	1/4	3	.57
PL 3/0-13	90211	13	3/0-6	10.17	.94	.69	1/4	2	.61
PL 3/0-14	90212	14	3/0-6	10.95	.94	.69	1/4	2	.66
PL 250-3	90301	3	250-6	2.69	1.12	.87	5/16	6	.18
PL 250-4	90302	4	250-6	3.55	1.12	.87	5/16	6	.24
PL 250-5	90303	5	250-6	4.41	1.12	.87	5/16	6	.30
PL 250-6	90304	6	250-6	5.27	1.12	.87	5/16	6	.33
PL 250-7	90305	7	250-6	6.14	1.12	.87	5/16	6	.42
PL 250-8	90306	8	250-6	7.00	1.12	.87	5/16	6	.48