

S4242B3225 | US2:S4242B3225

SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 42 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (225A) 10KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Image similar

Product

Article Number (Market Facing Number)	S4242B3225 US2:S4242B3225
Product Description	SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 42 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (225A) 10KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.
Product family	MB
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group	V22
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : EAR99
Standard lead time ex-works	2 Day/Days
Net Weight (lb)	40.08 lb
Product Dimensions (W x L x H)	Not available
Packaging Dimension	4.724 x 15.748 x 46.457
Package size unit of measure	in
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	662643926811
Commodity Code	8537109050
LKZ_FDB/ CatalogID	LV10.1
Product Group	5197
Country of origin	Mexico
Compliance with the substance restrictions according to RoHS directive	not available
Returnable	Yes
WEEE (2012/19/EU) Take-Back Obligation	No

Classifications

	Version	Classification
eClass	6	27-37-92-01
eClass	7.1	27-37-92-01
eClass	8	27-37-92-01
eClass	9	27-37-92-01
eClass	9.1	27-37-92-01
ETIM	5	EC002498
ETIM	6	EC002498
ETIM	7	EC002498
UNSPSC	15	39-12-11-01