



8-Port Fast Ethernet PoE+ Switch

8 x PoE ports, IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE), Endspan, Desktop
Part No.: **560764**

Save installation time and money with PoE.

The Intellinet 8-Port Fast Ethernet PoE+ Switch (560764) is designed to pass both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with eight Fast Ethernet ports (all of which support 802.3at/af PoE/PoE+), this switch can power wireless LAN access points and bridges, VoIP phones, IP video cameras and more while delivering network speeds of up to 100 Mbps.

Power over Ethernet 802.3at

The Intellinet 8-Port Fast Ethernet PoE+ Switch supports the IEEE 802.3at protocol and is designed to inject up to 30 watts of power per port*. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch require no additional power, thus eliminating the time and expense of electrical rewiring and minimizing the unsightly clutter caused by power supplies and adapters in awkward places such as ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short circuit, overload and high-voltage protection function, your equipment is well protected. For devices that are not 802.3at/af compliant (legacy wireless access points or network cameras), we suggest use of an Intellinet PoE/PoE+ Splitter.

* Total PoE budget for this switch is 66 watts. Per-port average power distribution is 8.25 watts; maximum per-port power usage cannot exceed 30 watts.

Features:

- Provides power and data connection for up to eight PoE network devices
- Save time and money by delivering data and power via existing network cables
- 10/100 auto-sensing ports automatically detect optimal network speeds
- IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- PoE power budget of 66 watts
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Store and forward switching architecture
- IEEE 802.3x flow control for full duplex
- Supports up to 4096 MAC address entries
- 160 kBytes buffer memory
- Desktop-size metal case

- Three-Year Warranty

Specifications:

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 10Base-T Cat3, 4, 5 UTP/STP RJ45
 - 100Base-TX Cat5 UTP/STP RJ45
- Packet filter/forwarding rate:
 - 148,800 pps (100 Mbps)
 - 14,880 pps (10 Mbps)
- MAC address table: 4096 entries
- Backplane speed: 1.6 Gbps
- Switch architecture: store and forward
- Certifications: FCC Class A, CE

LEDs

- PoE
- Power
- Link/activity

Power

- Input: 100 – 240 V AC, 50 – 60 Hz
- Power consumption: 70 watts (maximum)

Environmental

- Metal housing
- Dimensions: 228 (W) x 123 (L) x 44 (H) mm (8.9 x 4.8 x 1.7 in.)
- Weight: 1.5 kg (3.3 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -20 – 90°C (-4 – 194°F)

Package Contents

- 8-Port Fast Ethernet PoE+ Switch
- Power cable
- User manual

