



Blackburn®

Service Entrance Splices
T&B Catalog Number:

UPC Number: IKL69
 78378605038
Status: Active
Description:

Aluminum 5 1/2" Service Entrance Compression Splice for Wire Range -
 End A: 4/0 ASCR, 4/0 Str., Pink, End B: 4/0 ASCR, 4/0 Str., Pink, Die: 840

Features

Use for combinations of aluminum-to-aluminum and aluminum-to-copper conductors. Can be used as a low-cost reducing sleeve.

Concave caps seal out dirt but are easily pierced when inserting conductor. Prefilled with Oxide Inhibitor.

Color-coded and marked for easy identification.

Standards compliant. Meets ANSI C119.4 requirements. Connectors are RUS listed.

General

Insulation Type	Insulated
Material	Aluminum
Barrel Length	Longer Length
Conductor Range A ASCR	4/0
Conductor Range A Str./Sol.	4/0 Str.
Conductor Range B ASCR	4/0
Conductor Range B Str./Sol.	4/0 Str.
Conductor A Color	Pink
Conductor B Color	Pink

Dimension Information

Length (inches)	5.5
Conductor A Diameter Max.	0.564
Conductor A Diameter Min.	0.522
Conductor B Diameter Max.	0.564
Conductor B Diameter Min.	0.522

Tooling

Die Series	840 Die Series
Hydraulic Dies	B49EA, 840 U-K840, U-249
Mechanical Dies	BY37, 840 W-K840, TX

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	17.7 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321