



UNF505-G 70450841318

Status: Active

Description:

UPC Number:

1 1/2 in. Dark Gray PVC Coated UNF Female Union, Steel-electrogalvanized, 3 piece. For hazardous and non-hazardous locations.

nized, 3 piece. For nazardous an	d non-nazardous locations.
Features	
	Coated with a nominal .002 in. (2 mil) blue urethane on the interior, before PVC Coating is applied. A minimum .040 in. (40 mil) PVC Coating is bonded to the exterior.
	Pressure sealing sleeves to protect the connection.
Application	3
	To connect conduit to conduit, or to provide a
	means for future modification of the conduit system.
General	,
Custom_Finish	unf_112
Trade Size (inches)	1 1/2
Material	Steel
Finish	PVC Coated
Color	Dark Gray
Dimension Information	
Overall Length (inches)	2 3/4
Overall Diameter (inches)	3 1/16
Technical Information	
Chemical Resistance Chart	Available on Website
Specifications	
Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website
Packaging	
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	278 lbs. per 100
Application Support	
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
Product Overview-Conduit Outlet Bodies	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website
Notes	





	Dimensional values are of uncoated fittings.
	Standard color is dark gray. Also available in white and light blue. Custom colors are also available upon request. Please contact Technical Services, 888-862-3289.
Certifications	
RoHS Compliance	Yes

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com