

Screw Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-J3				1492-J4				1492-J6			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.												
Specifications	Feed-through terminal block				Feed-through terminal block				Feed-through terminal block			
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	690V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	25 A	20 A	24 A	21 A	35 A	25 A	32 A	28 A	50 A	41 A	36 A	
Wire Range (Rated Cross Section)	#22...12 AWG	#26...12 AWG	2.5 mm ²	2.5 mm ² (#20...14 AWG)	#22...10 AWG	#26...10 AWG	4 mm ²	4 mm ² (#20...12 AWG)	#22...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	
Wire Strip Length	0.39 in. (10 mm)				0.39 in. (10 mm)				0.47 in. (12 mm)			
Recommended Tightening Torque	4.5...7.1 lb•in (0.5...0.8 N•m)				9.0 lb•in (1.0 N•m)				14.2 lb•in (1.6 N•m)			
Density	59 pcs/ft (196 pcs/m)				49 pcs/ft (163 pcs/m)				37 pcs/ft (123 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks		Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.			Cat. No.	Pkg Qty.	
Color:	Grey	1492-J3	100			1492-J4	100			1492-J6	100	
	Red	1492-J3-RE	100			1492-J4-RE	100			1492-J6-RE	100	
	Blue	1492-J3-B	100			1492-J4-B	100			1492-J6-B	100	
	Black	1492-J3-BL	100			1492-J4-BL	100			1492-J6-BL	100	
	Green	1492-J3-G	100			1492-J4-G	100			1492-J6-G	100	
	Yellow	1492-J3-Y	100			1492-J4-Y	100			1492-J6-Y	100	
	Orange	1492-J3-OR	100			1492-J4-OR	100			1492-J6-OR	100	
	Brown	1492-J3-BR	100			1492-J4-BR	100			1492-J6-BR	100	
	White	1492-J3-W	100			1492-J4-W	100			1492-J6-W	100	
	Violet	1492-J3-V	100			1492-J4-V	100			—	—	
Mounting Rails:												
1 m Symmetrical DIN (Steel)		199-DR1	10			199-DR1	10			199-DR1	10	
1 m Symmetrical DIN (Aluminum)		1492-DR5	10			1492-DR5	10			1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2			1492-DR6	2			1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2			1492-DR7	2			1492-DR7	2	
End Barriers	Grey	1492-EBJ3	50			1492-EBJ3	50			1492-EBJ3	50	
	Blue	1492-EBJ3-B	50			1492-EBJ3-B	50			1492-EBJ3-B	50	
	Yellow	1492-EBJ3-Y	50			1492-EBJ3-Y	50			1492-EBJ3-Y	50	
End Anchors and Retainers:												
DIN Rail — Normal Duty		1492-EAJ35	100			1492-EAJ35	100			1492-EAJ35	100	
DIN Rail — Heavy Duty		1492-EAHJ35	50			1492-EAHJ35	50			1492-EAHJ35	50	
Screwless End Retainer		1492-ERL35	20			1492-ERL35	20			1492-ERL35	20	
Jumpers:*												
Screw Center Jumper — 10-pole		1492-CJJ5-10	20			1492-CJJ6-10	20			1492-CJJ8-10	20	
Screw Center Jumper — 4-pole		1492-CJJ5-4	50			1492-CJJ6-4	50			1492-CJJ8-4	50	
Screw Center Jumper — 3-pole		1492-CJJ5-3	50			1492-CJJ6-3	50			1492-CJJ8-3	50	
Screw Center Jumper — 2-pole		1492-CJJ5-2	50			1492-CJJ6-2	50			1492-CJJ8-2	50	
Plug-in Center Jumper — 50-Pole		1492-CJLJ5-50	10			1492-CJLJ6-41 (41-pole)	10			—	—	
Plug-in Center Jumper — 10-Pole		1492-CJLJ5-10	20			1492-CJLJ6-10	20			—	—	
Plug-in Center Jumper — 9-Pole		1492-CJLJ5-9	20			—	—			—	—	
Plug-in Center Jumper — 8-Pole		1492-CJLJ5-8	20			—	—			—	—	
Plug-in Center Jumper — 7-Pole		1492-CJLJ5-7	20			—	—			—	—	
Plug-in Center Jumper — 6-Pole		1492-CJLJ5-6	20			—	—			—	—	
Plug-in Center Jumper — 5-Pole		1492-CJLJ5-5	20			—	—			—	—	
Plug-in Center Jumper — 4-Pole		1492-CJLJ5-4	60			1492-CJLJ6-4	60			—	—	
Plug-in Center Jumper — 3-Pole		1492-CJLJ5-3	60			1492-CJLJ6-3	60			—	—	
Plug-in Center Jumper — 2-Pole		1492-CJLJ5-2	60			1492-CJLJ6-2	60			—	—	
Insulated Side Jumper — 24-Pole		1492-SJ5B-24	50			—	—			—	—	
Insulated Side Jumper — 10-Pole		1492-SJ5B-10	50			—	—			—	—	
Screw Type Jumper Notching Tool		1492-T1	1			1492-T1	1			1492-T1	1	
Other Accessories:												
Partition Plate		1492-EBJ16	20			1492-EBJ16	20			1492-EBJ16	20	
Test Plug Socket		1492-TPS23	20			1492-TPS23L	50			1492-TPS23L	50	
Test Plug		1492-TP23	20			1492-TP23	20			1492-TP23	20	
Test Plug (Stackable)		1492-TPJ5	25			1492-TPJ6	25			—	—	
Electrical Warning Plate		1492-EWPJ5	25			1492-EWPJ5	25			1492-EWPJ8	50	
Marking Systems:		1492-M5X12 (144/card)	5			1492-M6X12 (120/card)	5			1492-MR8X12 (84/card)	5	
Snap-in Marker Cards		1492-M5X5 (200/card)	5			1492-M6X5 (200/card)	5			1492-M8X5 (160/card)	5	

* Use of center jumpers may affect spacings, requiring derating of terminal blocks. See page 12-83 for details.