# 90° Bushed & 90° Corner Pull-in Conduit Elbows

# **Threaded For Rigid Conduit & IMC**

## Type 9

#### Features:

- · Available with insulated throat
- Threaded for rigid conduit, Female NPT Male NPS
- Telephone elbow, floor outlet fittings

#### Material/Finish:

Malleable Iron/Zinc Electroplated

#### Optional Finish:

For additional corrosion protection, specify Mechanically Galvanized.

Contact your local representative for pricing and availability.

#### **Third Party Certification:**



UL Listed: E-11853 and 11857




CSA Certified: 009795

#### **Applicable Third Party Standards:**

UL Standard: 514B CSA Standard: C22.2 No. 18 Fed. Spec: W-F-408E ANSI/NEMA: FB-1

Trade Size (inches)		Insulated Throat Catalog Number	Dimen <b>A</b>	sions in I B	nches C
1/ <sub>2</sub>	9-50	9-50T	1 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub> 2 <sup>3</sup> / <sub>16</sub> 2 <sup>1</sup> / <sub>2</sub> 3	11/ <sub>16</sub>
3/ <sub>4</sub>	9-75	9-75T	2 <sup>15</sup> / <sub>16</sub>		3/ <sub>4</sub>
1	9-100	9-100T	2 <sup>1</sup> / <sub>2</sub>		13/ <sub>16</sub>
11/ <sub>4</sub>	9-125	9-125T	3		7/ <sub>8</sub>





Type 9

# Type CE

#### Material/Finish:

Malleable Iron/Zinc Electroplated

### Third Party Certification:



UL Listed: E-11853

# **Applicable Third Party Standards:**

UL Standard: 514B NEMA: FB-1

		Catalog	Dimension	s in Inches
		Number	<b>A</b>	B
	½ ¾ 1	CE-050 CE-075 CE-0100	2½ 2¾ 3¼	2 2½ 2¾ 2¾

