Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.578

Date : Jan 21, 2017

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.578 - WM362412NC

created: 21.01.2017 build on www.rittal.com/us-en

Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

Product features

Dimensions:	Height: 900 mm (35 ˝) Width: 600 mm (24 ˝) Depth: 300 mm (12 ˝)
Material thickness::	Housing: 1.5 mm (0.06 ˝) Door: 2 mm (0.08 ˝) Mounting plate: 2.5 mm (0.1 ˝)
Mounting plate:	Height: 870 mm (34 ˝) Width: 549 mm (22 ˝)

© Rittal 2017

Packaging unit:	1 pc(s).
Weight/packaging unit:	40 kg (88.2 lb.)
EAN:	83155

Approvals

Approvals:	UL

2017 © Rittal Corporation