

LENGTH	NOMINAL LENGTH (IN)	WATTS	PRODUCT CODE	DESCRIPTION	CASE QTY	RATED LIFE (3 HRS/START)*	RATED LIFE (12 HRS/START)*	INITIAL LUMENS^	MEAN LUMENS^	COLOR TEMP (K)	CRI
Standard											
2'	22	24	46699	F24W/T5/830/ECO	40	30,000	36,000	2,000	1,840	3,000	85
	22	24	46700	F24W/T5/835/ECO	40	30,000	36,000	2,000	1,840	3,500	85
	22	24	46701	F24W/T5/841/ECO	40	30,000	36,000	2,000	1,840	4,100	85
	22	24	46702	F24W/T5/850/ECO	40	30,000	36,000	1,900	1,740	5,000	85
	22	24	46703	F24W/T5/865/ECO	40	30,000	36,000	1,880	1,740	6,500	85
3'	33	39	46744	F39W/T5/830/ECO	40	30,000	36,000	3,500	3,220	3,000	85
	33	39	46745	F39W/T5/835/ECO	40	30,000	36,000	3,500	3,220	3,500	85
	33	39	46746	F39W/T5/841/ECO	40	30,000	36,000	3,500	3,220	4,100	85
	33	39	46747	F39W/T5/850/ECO	40	30,000	36,000	3,350	3,080	5,000	85
	33	39	46748	F39W/T5/865/ECO	40	30,000	36,000	3,330	3,060	6,500	85
4'	45	54	46759	F54W/T5/830/ECO	40	30,000	36,000	5,000	4,600	3,000	85
	45	54	46760	F54W/T5/835/ECO	40	30,000	36,000	5,000	4,600	3,500	85
	45	54	46761	F54W/T5/841/ECO	40	30,000	36,000	5,000	4,600	4,100	85
	45	54	46762	F54W/T5/850/ECO	40	30,000	36,000	4,800	4,410	5,000	85
	45	54	46763	F54W/T5/865/ECO	40	30,000	36,000	4,750	4,370	6,500	85
5'	57	80	46802	F80W/T5/830/ECO	40	30,000	36,000	7,000	6,440	3,000	85
	57	80	46803	F80W/T5/835/ECO	40	30,000	36,000	7,000	6,440	3,500	85
	57	80	46804	F80W/T5/841/ECO	40	30,000	36,000	7,000	6,440	4,100	85
	57	80	46805	F80W/T5/850/ECO	40	30,000	36,000	6,700	6,160	5,000	85
	57	80	46806	F80W/T5/865/ECO	40	30,000	36,000	6,650	6,110	6,500	85
Watt-Miser®											
4'	45	51	71627	F54T5/830/WM/ECO	40	30,000	36,000	5,000	4,600	3,000	85
	45	51	71628	F54T5/835/WM/ECO	40	30,000	36,000	5,000	4,600	3,500	85
	45	51	71629	F54T5/841/WM/ECO	40	30,000	36,000	5,000	4,600	4,100	85
	45	51	71630	F54T5/850/WM/ECO	40	30,000	36,000	4,790	4,410	5,000	85
	45	51	71631	F54T5/865/WM/ECO	40	30,000	36,000	4,750	4,370	6,500	85
4'	45	47	62020	F54T5/47W/830ECO	40	30,000	36,000	4,800	4,410	3,000	84
	45	47	62021	F54T5/47W/835ECO	40	30,000	36,000	4,800	4,410	3,500	84
	45	47	62022	F54T5/47W/841ECO	40	30,000	36,000	4,800	4,410	4,100	84
	45	47	62023	F54T5/47W/850ECO	40	30,000	36,000	4,600	4,230	5,000	84
	45	47	62024	F54T5/47W/865ECO	40	30,000	36,000	4,550	4,180	6,500	84
Extra-Life											
4'	45	54	68836	F54T5/XL/830/ECO	40	50,000	60,000	5,000	4,600	3,000	84
	45	54	68837	F54T5/XL/835/ECO	40	50,000	60,000	5,000	4,600	3,500	84
	45	54	68838	F54T5/XL/841/ECO	40	50,000	60,000	5,000	4,600	4,100	84
	45	54	68839	F54T5/XL/850/ECO	40	50,000	60,000	4,800	4,410	5,000	84
	45	54	68840	F54T5/XL/865/ECO	40	50,000	60,000	4,750	4,370	6,500	84
covRguard®											
2'	22	24	71000	F24W/T5/830/ECO/CVG	40	30,000	36,000	1,950	1,853	3,000	85
	22	24	70998	F24W/T5/835/ECO/CVG	40	30,000	36,000	1,950	1,853	3,500	85
	22	24	70997	F24W/T5/841/ECO/CVG	40	30,000	36,000	1,950	1,853	4,100	85
	22	24	70999	F24W/T5/850/ECO/CVG	40	30,000	36,000	1,850	1,758	5,000	85
	22	24	70996	F24W/T5/865/ECO/CVG	40	30,000	36,000	1,800	1,710	6,500	85
3'	33	39	70995	F39W/T5/830/ECO/CVG	40	30,000	36,000	3,400	3,230	3,000	85
	33	39	70994	F39W/T5/835/ECO/CVG	40	30,000	36,000	3,400	3,230	3,500	85
	33	39	70993	F39W/T5/841/ECO/CVG	40	30,000	36,000	3,400	3,230	4,100	85
	33	39	70990	F39W/T5/865/ECO/CVG	40	30,000	36,000	3,250	3,040	6,500	85
4'	45	54	48433	F54T5/830/HO/ECO/CVG	40	30,000	36,000	4,850	4,560	3,000	85
	45	54	48436	F54T5/835/HO/ECO/CVG	40	30,000	36,000	4,850	4,560	3,500	85
	45	54	48458	F54T5/841/HO/ECO/CVG	40	30,000	36,000	4,850	4,560	4,100	85
	45	54	80311	F54T5/850/HO/ECO/CVG	40	30,000	36,000	4,650	4,370	5,000	85
	45	54	48469	F54T5/865/HO/ECO/CVG	40	30,000	36,000	4,650	4,320	6,500	85
Watt-Miser® with covRguard®											
4'	45	51	72986	F54T5/835/WM/ECO/CVG	40	30,000	36,000	4,850	4,560	3,500	85
	45	51	72987	F54T5/841/WM/ECO/CVG	40	30,000	36,000	4,850	4,560	4,100	85
	45	51	72988	F54T5/850/WM/ECO/CVG	40	30,000	36,000	4,650	4,370	5,000	85
	45	47	65106	F54T5/47W/841CVG	40	30,000	36,000	4,728	4,343	4,100	84
	45	47	65107	F54T5/47W/850CVG	40	30,000	36,000	4,531	4,167	5,000	84
Cold temperature											
4'	45	54	81522	F54T5/841/CT	36	30,000	36,000	4,500	4,275	4,100	85

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

*Rated life is given for programmed Rapid Start ballasts. Life ratings are based on engineering data with lamps cycled every 3 or 12 operating hours.
 ^T5 Starcoat® Ecolux® lamp initial and mean lumen ratings reflect light output at 95° F (35° C).
 Note: All T5 lamps included in product charts have a Miniature Bi-Pin (G5) base.

Get more information at
GELighting.com/LFL