

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	30W
120V	0.24A	Color Temp	4000K (Neutral)
208V	0.15A	Color Accuracy	80 CRI
240V	0.13A	L70 Lifespan	50,000 Hours
277V	0.11A	Lumens	3,284
Input Watts	27.90W	Efficacy	117.7 lm/W

Technical Specifications

Compliance

UL Listed:

Suitable for damp locations

Construction

IC Rated:

Suitable for direct contact with insulation

Ambient Operating Temperature:

-20°C (-4°F) to 40°C (104°F)

Lens:

Frosted Polystyrene

Housing:

Plastic frame & galvanized steel back housing

Finish:

White

Mounting:

Recessed into T-grid ceiling. Surface and recessed mounting kits available for drywall ceilings.

Green Technology:

Mercury and UV free. RoHS-compliant components.

Listings

CCEA Compliant:

Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

IESNA LM-70 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PW4WLM0M

LED Characteristics

LEDs:

Long-life, high-efficiency, surface-mount LEDs

Performance

Lifespan:

50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Electrical

Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz, 2kV surge protection, 120V: 0.24A, 208V: 0.15A, 240V: 0.13A, 277V: 0.11A

Technical Specifications (continued)

Electrical

THD:

9.71% at 120V, 11.54% at 277V

Power Factor:

98.8% at 120V, 93.8% at 277V

Dimming:

0-10V, standard down to 10%

Note:

All values are typical (tolerance +/- 10%)

Other


5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Integrated 0-10V dimming

50,000-Hour LED lifespan

5-year, limited warranty

4 per case, must order in case quantity increments

Ordering Matrix

Family	Housing Size	Wattage	Color Temp/CCT	Voltage	Lightcloud		
T34	-	2X2	-	30	N	/D10	
		2X2 = 2' X 2'		20 = 20W ¹	Blank = 5000K	/D10 = 0-10V Dimming	Blank = No Options
		2X4 = 2' X 4'		30 = 30W	N = 4000K		/LC = Lightcloud® Control
				40 = 40W	YN = 3500K		
				50 = 50W ²			

Must order in case quantity increments. See product spec sheet for exact increments.

¹ Available only in 2' x 2' only.

² Available in 2' x 4' only.