Standard grade toggle switches

Product description

Single-pole, 3-way, 4-way
15A,120V/AC

1303

Design features

- 3-way switches feature additional push-in common termination for feed-through tapping

- Push-in terminals accept #14 AWG solid wire only; side wire terminals accept up to #10 AWG solid wire

- Long, broad mounting strap virtually eliminates floating installations

- Patented built-in wire stripper for #12 and #14 AWG wire to speed installation

- Patented built-in wire looper for pre-looping

- Tri-combo screws accept Slotted, Phillips, and Robertson-head tools for installation flexibility

- Lighted toggle glows in "OFF" position

1301-7

Toggle switches, non-grounding   cULus NOM 426

Rating A	V/AC	Description	Color suffix	Catalog no.	🇺🇸	✓
15	120	Single-pole, side wire & push wire	B, BK, LA, V, W	☐ 1301__	•	•
		3-way, back wire, side wire & push wire	B, BK, LA, V, W	☐ 1303__	•	•

cULus Listed to UL20, file no. E18704; 7504 also UL Listed to Federal Spec WS-896E

Toggle switches, grounding   UL CSA NOM 426

Rating A	V/AC	Description	Color suffix	Catalog no.	🇺🇸	✓
15	120	Single-pole, side wire & push wire	A, B, BK, LA, V, W	☐ 1301-7__	•	•
		Single-pole, side wire & push wire, auto ground	A, B, BK, LA, V, W	☐ 1301-9__	•	•
		3-way, back wire, side wire & push wire	A, B, BK, LA, V, W	☐ 1303-7__	•	•
		3-way, side wire & push wire, auto ground	A, B, BK, LA, V, W	☐ 1303-9__	•	•
		4-way, side wire & push wire	A, B, BK, LA, V, W	☐ 1242-7__		
		Single-pole, less ears, side wire & push wire	A, B, BK, LA, W	☐ 1301-73__	•	•
		Lighted, single-pole, side wire & push wire	LA, V, W	☐ 1301-7LT__	•	
		Lighted, 3-way, side wire & push wire	V, W	☐ 1303-7LT__	•	

cULus Listed to UL20, file no. E18704; NOM certified. Lighted models also CSA certified to C22.2, no. 111

1301-73

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), W (White)

A	B	BK	LA	V	W
(Almond)	(Brown)	(Black)	(Lt. Almond)	(Ivory)	(White)

Dimensional information: B-68 **Specification information:** Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

🇺🇸 Indicates NAFTA compliant - Page G-21   ✓ RoHS compliant - Page G-21