



[Catalog Home](#)

**Product Datasheet**

**CHANCE**

**6346 -- No-Wrench Anchor**



No-Wrench 66" (1676 mm) long with 6" (152 mm) Helix Tripleye

**Product Specifications**

<b>Anchor Style</b>	No Wrench Screw Anchor
<b>Component</b>	No Wrench Screw Anchor
<b>Single Helix Diameter</b>	6" (152 mm)
<b>Number of Helices</b>	1
<b>Eye Nut Style</b>	Tripleye
<b>Rod Diameter</b>	0.75" (19.1 mm)
<b>Length</b>	66" (1676 mm)
<b>Torque Rating</b>	400 Ft Lbs (542 N-M)
<b>Coating</b>	Galvanized
<b>Installation Tool</b>	E303-0255
<b>Industry Standards</b>	RUS Accepted
<b>Material Type</b>	Standard
<b>UPC Code</b>	09635907298
<b>Standard Package</b>	1
<b>Standard Package Unit</b>	EA
<b>Min Order Qty</b>	1
<b>Weight / Ea.</b>	11.27 lbs
<b>Webpage</b>	Click <a href="#">HERE</a> to view the web page.
<b>Drawing</b>	Click <a href="#">HERE</a> to view drawing.

**Notes**

Caution: All components of the Chance anchoring system are performance mated. Use of other anchoring products or equipment will not necessarily produce the same results.

**Compressed Product Number**

6346

**Holding Strength v. Soil Class**

Catalog No. Tripleye	Anchor Size Diameter	Rod Dia. & Length	No Wrench Anchor Holding Strength vs Chance Soil Class		
			Class 5	Class 6	Class 7
4345 or 43451	4"	3/4" x 54"	4,500	3,000	1,500
6346 or 63461	6"	3/4" x 66"	6,500	5,000	2,500
PS816 or 8161	8"	1" x 66"	11,000	9,000	6,000
10146	10"	1-1/4" x 66"	13,000	10,000	7,000
10148	10"	1-1/4" x 96"	13,000	10,000	7,000
12537	12"	1-1/4" x 96"	16,000	15,000	12,000
15148	15"	1-1/4" x 96"	19,000	17,000	14,000

[Catalog Home](#)

[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.