

S7-300 FRONT CONNECTOR 20 TO DB50F 3M
 Cable with front connector for SIMATIC S7-300 20 pole (6ES7392-1AJ00-0AA0) on 25 pole D-SUB socket for ET200M; 0.50 mm²
 Length = 3 m

Target system	SIMATIC S7-300 PCS7 MTA
Product type designation	MTA
Product designation	Pre-assembled front connector MTA

Product properties, functions, components / general

Wire length	3 m
Design of cable	Round cable
Material / of the connecting cable sheath	PVC
Color / of cable sheath	Black
Outer diameter / of cable sheath	10.6 mm; bundled single cores
Conductor cross section / Rated value	0.5 mm ²
Number of channels	20
Number of poles	20; of the front connector

Operating data

Operating voltage / at DC	
<ul style="list-style-type: none"> Rated value 	24 V
<ul style="list-style-type: none"> maximum 	30 V
Ambient temperature	
<ul style="list-style-type: none"> during storage 	-30 ... +70 °C
<ul style="list-style-type: none"> during operation 	0 ... 60 °C

General data

Certificate of suitability / cULus approval	No
Suitability for interaction	
<ul style="list-style-type: none"> Input card PLC 	Yes
<ul style="list-style-type: none"> PLC output card 	No
Suitability for use	
<ul style="list-style-type: none"> digital signal transmission 	No
<ul style="list-style-type: none"> analog signal transmission 	Yes
Type of electrical connection	
<ul style="list-style-type: none"> in the field 	Connector strip
<ul style="list-style-type: none"> on enclosure 	Screw-type terminal
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	0.921 kg