

K4100 & K4400 Series Thermal-Type Photo Controls with Stem Mounting

- Single and multi-volt models
- Dusk-to-Dawn lighting control
- Delay feature prevents unwanted OFF switching
- Lightlevel slide adjustment
- Cadmium sulfide photocell
- 1/2"-14 threaded stem
- Washer gasket and locking nut included



Model #	Watts Tungsten	VA Ballast	Amps Tungsten	Amps Ballast	Input Voltage	Agency/Listing	Warranty
C. K4121C	1800	1000	15	8.3	120 VAC		2 year
K4123C	3100-4150	1700-2300	15	8.3	208-277 VAC		2 year
K4127	5205	2880	15	8.3	347 VAC		2 year
K4135	7200	4000	15	8.3	480 VAC	-	2 year
K4141C	3000	3000	25	25	120 VAC	-	1 year
D. K4421M*	1800	1000	15	8.3	120 VAC		2 year
K4423M*	3100-4150	1700-2300	15	8.3	208-277 VAC		2 year
K4136M*	2000-4625	1800	16.7	15	120 or 277 VAC		2 year

*Models with "M" suffix have heavy-duty die cast housing

Rating:

Dimensions: 1 9/16" (4.0 cm) Sq x 3" (7.6 cm) L

Power Consumption: Under 1 W

Operating Temperature: -40°F to 158°F (-40°C to 70°C)

Screw-In Photo Control

- Controls interior and exterior lights
- ON at dusk, OFF at dawn
- Accommodates any incandescent light
- Limited 1-year warranty

Model #	Voltage	Watts
NE1C	120 VAC/60 Hz	150 Max

Note: Not for use with CFL and LED lights

