

# ELECTRONIC FLUORESCENT BALLASTS

## For 25W-36" T8 Lamps

HIGH POWER FACTOR SOUND RATED A



No. of Lamps	Input Volts	Lamp Starting Method	Ballast Family	Catalog Number	Input Power ANSI (Watts)	Ballast Factor	Max. THD %	Line Current (Amps)	Min. Starting Temp. (°F/°C)	Dim.	Wiring Dia.	
<b>F25T8, FBO24T8 (25W - 36")</b>												
1	120	IS	AmbiStar <sup>‡</sup>	REB-2P32-SC	26	1.00	150	0.39	0/-18	B	*64	
	120-277	IS	Centium	ICN-1P32-MC	23	0.88	15	0.19-0.09	0/-18	A2	63	
				ICN-1P32-N	26	0.91	10	0.22-0.10		N		*64
				ICN-2P32-N	29	1.06	15	0.24-0.11			-20/-29	N
			IOP-1P32-LW-N	21	0.78	10	0.17-0.08	N				
			IOPA-1P32-LW -N									
			IOP-1P32-N	23	0.88	10	0.20-0.09	N				
			IOPA-1P32-N									
			IOP-1P32-HL-SC	30	1.22	10	0.26-0.11	B				
			IOPA-1P32-HL-N									
		IOP-2P32-LW-N	24	0.90	10	0.20-0.09	N					
		IOPA-2P32-LW-N										
		IOP-2P32-N	28	1.05	10	0.23-0.10	N					
		IOPA-2P32-N										
		IOP-2P32-HL-N	35	1.40	20	0.29-0.13	N					
		IOPA-2P32HL-N										
		PS	IOP-1PSP32-LW-N	20	0.74	10	0.16-0.07	0/-18	N	20		
			IOP-1PSP32-N	22	0.92	10	0.19-0.08					
			IOP-2PSP32-LW-N	21	0.77	10	0.17-0.08			77		
	IOP-2PSP32-N		25	0.97	10	0.21-0.10						
	IOP-2PSP32-HL-N		35	1.35	10	0.29-0.13						
	347	IS	Optanium	GOPA-1P32-LW-SC	20	0.80	10	0.07	-20/-29	B	63	
				GOPA-1P32-SC	22	0.91						0.07
				GOPA-2P32-LW-SC	24	0.88					0.08	
				GOPA-2P32-SC	27	1.05						0.08
		GOP-2PSP32-LW-SC		26	0.77	0.08						
		GOP-2PSP32-SC		26	1.05			0.08	0/-18	77		
HOP-2PSP32-HL-L		35		1.30	0.11-0.09	L						
347-480	PS											

<sup>‡</sup> The above AmbiStar ballasts are normal power factor and labeled 'For Residential Use Only'

Refer to page 3-38 and 3-39 for dimensions  
 Refer to page 3-40 and 3-41 for wiring diagrams  
 Refer to pages 9-23 to 9-27 for lead lengths and shipping data