

# SYLVANIA Luminaires

## ValueLED™ Slim Floodlight

### Application

The Slim Floodlight luminaires are lightweight, compact and designed for landscape, flood and signage applications.

### Benefits and Features

- Compact profile for discrete exterior illumination
- IP65 rated with wide flood distribution
- Adjustable 1/2" NPS knuckle arm
- Meets DLC requirements to maximize rebate opportunities
- Up to 117 LPW
- 4000K and 5000K color temperature
- CRI > 80
- Offered in 30 and 50 watts
- Energy savings up to 80%

### Electrical

- 120-277V<sub>AC</sub>
- Power Factor > 90%
- THD < 20%

### Rated Life

- 150,000 hours (L<sub>70</sub>)

### Warranty

- 5-year

### Ambient Operating Range

- -40°F to +104°F (-40°C to +40°C)

### Certifications and Listings

- cULus
- RoHS compliant
- FCC
- DLC

Item #
Type
Project
Notes
Date



### Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
150W Inc	150	30	80%
50W HPS	62	30	52%
70W HPS	91	30	67%
100W HPS	120	30	67%
100W MH	130	30	69%
300W Inc	300	50	83%
150W HPS	170	50	71%
150W MH	188	50	73%
175W MH	210	50	76%

### Installation

- ValueLED Slim Floodlight luminaires can be knuckle mounted with included 1/2" NPS for mounting to junction box (please see Ordering Information).



## Ordering Guide

<b>SLMFLD</b>	<b>2A</b>	<b>/</b>	<b>XXX</b>	<b>UNV</b>	<b>8</b>	<b>XX</b>	<b>/</b>	<b>WF</b>	<b>KN</b>	<b>/</b>	<b>XX</b>
SLMFLD = Slim Floodlight	Generation 2A		Wattage 30 = 30 Watts 50 = 50 Watts	Voltage UNV = 120-277V	CRI 8 = >80	Color Temp (CCT) 40 = 4000K 50 = 5000K		Distribution WF = Wide Flood	Mounting KN = Knuckle Mounting		Color/Finish BZ = Bronze

## Ordering Information


Item Number	Ordering Abbreviation	Wattage	Input Voltage	CRI	Color Temp	Total Fixture Lumens	LPW	DLC*	Mounting	Color
61177	SLMFLD2A/030UNV840/WFKN/BZ	30	120-277	>80	4000K	3400	114	Std	Knuckle	Bronze
61178	SLMFLD2A/030UNV850/WFKN/BZ	30	120-277	>80	5000K	3400	114	Std	Knuckle	Bronze
61179	SLMFLD2A/050UNV840/WFKN/BZ	50	120-277	>80	4000K	5700	117	Std	Knuckle	Bronze
61180	SLMFLD2A/050UNV850/WFKN/BZ	50	120-277	>80	5000K	5700	117	Std	Knuckle	Bronze

\*Std for DLC Standard

## Photometric Data


### SLMFLD2A/030UNV840

FC at 10' mounting height when aimed at 30 degrees




### SLMFLD2A/050UNV840

FC at 10' mounting height when aimed at 30 degrees




## Physical Information

### 30W



### 50W



### Luminaire

Description	Length	Width	Height
30W Knuckle Mount	7.2"	1.9"	9.2"
50W Knuckle Mount	8.5"	2.1"	10.2"

### EPA

30W	0.33ft <sup>2</sup>
50W	0.45ft <sup>2</sup>

## Mounting Accessories

Item Number	Ordering Abbreviation	Item Description
61792	SLMFLD2A/TRUNNION/MED/BZ	Trunnion mount accessory for NAEDs 61179 and 61180
65243	SLMFLD2A/TRUNNION/SML/BZ	Trunnion mount accessory for NAEDs 61177 and 61178

LEDVANCE LLC  
200 Ballardvale Street  
Wilmington, MA 01887 USA  
Phone 1-800-LIGHTBULB (1-800-544-4828)  
[www.sylvania.com](http://www.sylvania.com)

SYLVANIA and LEDVANCE are registered trademarks.  
All other trademarks are those of their respective owners.  
Licensee of product trademark SYLVANIA in general lighting.  
Specifications subject to change without notice.

 /sylvania  /sylvania

Name: \_\_\_\_\_  
Email: \_\_\_\_\_  
Phone: \_\_\_\_\_

