



**Catalog No. AEU3424RCXAXT1B4**

**Description: PRO-STK 480V 3PH 400A FT 42CR CU**

**UPC No 783175120321**

**Products > Panelboards > A-Series > Pro-Stock Lighting Panel**

- Maximum system voltage is upto 480Vac for AE panelboard line
- Field installable kits allow you to shift gears on the fly
- Standard Pro-Stock panels have the capability of adding sub-feed breakers or feed-thru lugs in the field
- All panel are convertible between main lugs or main breakers
- Reversible interior. No need to specify top or bottom feed
- Solid-state Spectra RMS or thermal magnetic breakers available as mains or sub-feeds
- NEMA 1 or 3R/12 enclosures available
- Flush or surface mounted trims with door within door and front hinge to box options available
- Extruded split neutrals speed and simplify wiring
- Main bus ratings of 225, 400 and 480 amps available
- Modular kits allow for field installation of 200% neutrals and Service Entrance bonding straps
- Field installable TVSS (Transient Voltage Surge Suppression) kits - 200ka per phase
- Up to six poles of sub-feed available in 400A and 600A, and up to 3 poles of sub-feed available in 225A
- Meets all UL, NEMA and CSA standards

**Descriptors**

Category	Pro-Stock Lighting Panel
GO Schedule	32

**Specifications**

Voltage	480 V
Phase	3
Panel Rating	400
No of Circuits	42
Feed Thru	Yes
Bus	Copper
Interior Type	AEU
Box/Front Height	76.0 in
Interior Description	Pro-Stock 480V, 3PH, 400A 42Cir. CU
GSA Compliance	No