



Series No.	Cone (Inner ring)	Page	Cup (Outer ring)	Page
11000R	11163R	59		
	11165XR	61		
	11165XSR	61		
11500	11590	103	11520	103
LM11700R	LM11749R	39	LM11710	39
LM11900	LM11949	39	LM11910	39
12000	12168	61	12303	61
	12175	61		
12500	12580	39	12520	39
M12600	M12648	41	M12610	41
	M12648A	41		
	M12649	41		
LM12700	LM12749	41	LM12711	41
13600	13682	53	13620	53,55
	13685	55	13621	55
	13686	55	13624	55
	13687	55		
13800	13889	55	13830	55,57
	13892	57	13836	55
14000	14116	47	14274	45,47
	14117A	45	14274A	45,47,49,51
	14118	45	14276	45,51
	14118A	45	14277	49
	14120A	45	14283	45
	14123A	47		
	14125	47		
	14130	49		
	14131	49		
	14136A	51		
	14137A	51		
	14138A	51		
	14139	51		
15000	15100	41,43	15243	41
	15101	41,43	15245	41,43,45,47
	15102	43	15250	43
	15103	43	15250R	43
	15106	43	15250X	43
	15112	43		
	15113	43		
	15116	45		
	15117	45		
	15118	47		
	15119	47		
	15120	47		
	15123	47		
	15125	47		
	15126	47		

Series No.	Cone (Inner ring)	Page	Cup (Outer ring)	Page
15500	15572	41	15520	41,43
	15578	41	15523	43
	15579X	43		
	15580	43		
	15590	43		
16000	16131	49	16282	53,55
	16137	51	16283	55
	16143	53	16284	49,51,53,55
	16150	55		
	16151	55		
17000	17098	41	17244	41,45
	17098X	41		
	17118	45		
	17118S	45		
	17119	45		
17500R	17580R	39	17520	39
17800	17887	65	17831	65
18000	18200	69	18337	69
18500	18587	57	18520	57,59
	18590	59		
	18591	59		
18600	18685	61	18620	61,65
	18690	65		
18700	18780	65	18720	65
	18790	69	18721	69
			18723	69
			18724	69
19000R	19138R	51	19268	51,53
	19143R	53	19268X	55
	19150R	55	19269	55
			19281	53,55
			19282	55
			19283	53,55
21000	21063	39	21212	39
	21075	39	21213	39
	21078	39		
L21500	L21549	39	L21511	39
23000	23092	103	23256	103
	23098	103		
	23100	103		
23600	23685	49	23620	49,51
	23690	51	23621	53
	23691	53	23623	53
24700R	24780R	59	24720	59
	24781R	59	24721	59
			24722	59

TS type
d (25.400) ~ (28.575) mm
(1.0000) ~ (1.1250) inch



$P = XF_r + YF_a$ $P_0 = 0.5 F_r + Y_0 F_a$ or $P_0 = F_r$			
$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y_1

Note) The Values of “e” “Y₁” and “Y₀” are given in the table below.

Boundary dimensions												Basic load ratings (kN)		Fatigue load limit		Bearing No.		Load center		Mounting dimensions						Con- stant	Axial load factors		Reference rating (kN)		Factor				
<i>d</i>		<i>D</i>		<i>T</i>		<i>B</i>		<i>C</i>		<i>r</i> ¹⁾ (min.)		<i>r</i> ₁ ¹⁾ (min.)		<i>C</i> _r	<i>C</i> _{0r}	(kN) <i>C</i> _u		Cone (Inner ring)	Cup (Outer ring)	<i>a</i>		<i>d</i> _a		<i>d</i> _b		<i>D</i> _a		<i>D</i> _b		<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₀	(500 rpm for 3 000 Hrs.)		<i>K</i>
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch							mm	inch	mm	inch	mm	inch	mm	inch	mm	inch				mm	inch	
25.400	1.0000	63.500	2.5000	19.050	0.7500	20.638	0.8125	14.288	0.5625	0.8	0.03	1.2	0.05	55.7	50.7	7.30		15101	15250R	13.2	0.52	32.5	1.28	31.5	1.24	55.0	2.17	59.0	2.32	0.35	1.71	0.94	12.9	7.75	1.67
	1.0000	63.500	2.5000	20.638	0.8125	20.638	0.8125	15.875	0.6250	3.6	0.14	1.2	0.05	55.7	50.7	7.30		15100	15250	15.0	0.59	38.0	1.50	31.5	1.24	55.0	2.17	59.0	2.32	0.35	1.71	0.94	12.9	7.75	1.67
	1.0000	63.500	2.5000	20.638	0.8125	20.638	0.8125	15.875	0.6250	3.6	0.14	1.6	0.06	55.7	50.7	7.30		15100	15250X	15.0	0.59	38.0	1.50	31.5	1.24	55.0	2.17	59.0	2.32	0.35	1.71	0.94	12.9	7.75	1.67
	1.0000	63.500	2.5000	20.638	0.8125	20.638	0.8125	15.875	0.6250	1.6	0.06	1.6	0.06	55.7	50.7	7.30		15102	15250X	15.0	0.59	34.0	1.34	31.5	1.24	55.0	2.17	59.0	2.32	0.35	1.71	0.94	12.9	7.75	1.67
	1.0000	64.292	2.5312	21.432	0.8438	21.432	0.8438	16.670	0.6563	1.6	0.06	1.6	0.06	69.1	70.7	9.90		M86643R	M86610	18.0	0.71	38.0	1.50	36.5	1.44	54.0	2.13	61.0	2.40	0.55	1.10	0.60	16.0	14.9	1.07
	1.0000	66.421	2.6150	23.812	0.9375	25.433	1.0013	19.050	0.7500	1.2	0.05	1.2	0.05	83.8	75.2	11.2		2687	2631	13.9	0.55	33.5	1.32	31.5	1.24	58.0	2.28	60.0	2.36	0.25	2.36	1.30	19.5	8.45	2.30
	1.0000	68.262	2.6875	22.225	0.8750	22.225	0.8750	17.462	0.6875	0.8	0.03	1.6	0.06	63.7	61.1	8.80		02473	02420	17.1	0.67	34.5	1.36	33.5	1.32	59.0	2.32	63.0	2.48	0.42	1.44	0.79	14.8	10.5	1.41
	1.0000	68.262	2.6875	22.225	0.8750	22.225	0.8750	17.462	0.6875	0.8	0.03	0.8	0.03	63.7	61.1	8.80		02473	02421	17.1	0.67	34.5	1.36	33.5	1.32	59.0	2.32	63.0	2.48	0.42	1.44	0.79	14.8	10.5	1.41
	1.0000	72.000	2.8346	19.000	0.7480	18.923	0.7450	15.875	0.6250	1.6	0.06	1.6	0.06	69.8	60.0	8.85		26100	26283	14.3	0.56	34.5	1.36	32.5	1.28	62.0	2.44	65.0	2.56	0.36	1.67	0.92	16.1	9.90	1.62
	1.0000	72.233	2.8438	25.400	1.0000	25.400	1.0000	19.842	0.7812	0.8	0.03	2.4	0.09	83.8	87.4	12.4		HM88630	HM88610	20.7	0.81	39.5	1.56	39.5	1.56	60.0	2.36	69.0	2.72	0.55	1.10	0.60	19.6	18.3	1.07
	1.0000	72.626	2.8593	24.608	0.9688	24.257	0.9550	17.462	0.6875	2.4	0.09	1.6	0.06	77.3	60.5	8.75		41100	41286	20.7	0.81	41.0	1.61	36.5	1.44	61.0	2.40	68.0	2.68	0.60	1.00	0.55	17.9	18.4	0.97
	1.0000	72.626	2.8593	30.162	1.1875	29.997	1.1810	23.812	0.9375	0.8	0.03	0.8	0.03	98.6	89.3	13.3		3189	3130	20.3	0.80	35.5	1.40	35.0	1.38	63.0	2.48	67.0	2.64	0.33	1.80	0.99	23.0	13.1	1.76
	1.0000	72.626	2.8593	30.162	1.1875	29.997	1.1810	23.812	0.9375	2.0	0.08	3.2	0.13	98.6	89.3	13.3		3189X	3120	20.3	0.80	37.5	1.48	35.0	1.38	61.0	2.40	67.0	2.64	0.33	1.80	0.99	23.0	13.1	1.76
	1.0000	80.000	3.1496	21.000	0.8268	22.403	0.8820	17.826	0.7018	0.8	0.03	1.2	0.05	85.0	74.8	11.4		338	332	15.1	0.59	36.5	1.44	35.0	1.38	73.0	2.87	75.0	2.95	0.27	2.20	1.21	19.6	9.15	2.14
	1.0000	80.000	3.1496	24.176	0.9518	22.403	0.8820	21.000	0.8268	0.8	0.03	2.4	0.09	85.0	74.8	11.4		338	332A	18.3	0.72	36.5	1.44	35.0	1.38	71.0	2.80	75.0	2.95	0.27	2.20	1.21	19.6	9.15	2.14
25.987	1.0231	50.292	1.9800	14.224	0.5600	14.732	0.5800	10.668	0.4200	3.6	0.14	1.2	0.05	39.1	37.0	5.15		L44645R	L44610	10.8	0.43	36.5	1.44	31.0	1.22	44.5	1.75	47.0	1.85	0.37	1.60	0.88	8.95	5.70	1.56
	1.0231	57.150	2.2500	17.462	0.6875	17.462	0.6875	13.495	0.5313	3.6	0.14	1.6	0.06	47.2	42.7	6.10		15579X	15520	12.7	0.50	38.5	1.52	32.0	1.26	51.0	2.01	53.0	2.09	0.35	1.73	0.95	10.8	6.40	1.69
26.157	1.0298	63.500	2.5000	20.638	0.8125	20.638	0.8125	15.875	0.6250	0.8	0.03	1.2	0.05	55.7	50.7	7.30		15103	15250	15.0	0.59	33.5	1.32	33.0	1.30	55.0	2.17	59.0	2.32	0.35	1.71	0.94	12.9	7.75	1.67
26.162	1.0300	66.421	2.6150	23.812	0.9375	25.433	1.0013	19.050	0.7500	1.6	0.06	1.2	0.05	83.8	75.2	11.2		2682	2631	13.9	0.55	34.5	1.36	32.0	1.26	58.0	2.28	60.0	2.36	0.25	2.36	1.30	19.5	8.45	2.30
26.975	1.0620	57.150	2.2500	19.845	0.7813	19.355	0.7620	15.875	0.6250	0.8	0.03	1.6	0.06	60.8	57.1	8.25		1987R	1922	13.9	0.55	32.5	1.28	31.5	1.24	51.0	2.01	53.5	2.11	0.33	1.82	1.00	14.0	7.90	1.77
26.987	1.0625	72.626	2.8593	24.608	0.9688	24.257	0.9550	17.462	0.6875	2.4	0.09	1.6	0.06	77.3	60.5	8.75		41106	41286	20.7	0.81	42.0	1.65	36.5	1.44	61.0	2.40	68.0	2.68	0.60	1.00	0.55	17.9	18.4	0.97
26.988	1.0625	50.292	1.9800	14.224	0.5600	14.732	0.5800	10.668	0.4200	3.6	0.14	1.2	0.05	39.1	37.0	5.15		L44649R	L44610	10.8	0.43	37.5	1.48	31.0	1.22	44.5	1.75	47.0	1.85	0.37	1.60	0.88	8.95	5.70	1.56
	1.0625	57.150	2.2500	19.845	0.7813	19.355	0.7620	15.875	0.6250	3.2	0.13	1.6	0.06	60.8	57.1	8.25		1997XR	1922	13.9	0.55	37.5	1.48	31.5	1.24	51.0	2.01	53.5	2.11	0.33	1.82	1.00	14.0	7.90	1.77
	1.0625	60.325	2.3750	19.842	0.7812	17.462	0.6875	15.875	0.6250	3.6	0.14	1.6	0.06	47.2	42.7	6.10		15580	15523	15.1	0.59	38.5	1.52	32.0	1.26	51.0	2.01	54.0	2.13	0.35	1.73	0.95	10.8	6.40	1.69
	1.0625	62.000	2.4409	19.050	0.7500	20.638	0.8125	14.288	0.5625	0.8	0.03	1.2	0.05	55.7	50.7	7.30		15106	15245	13.2	0.52	33.5	1.32	33.0	1.30	55.0	2.17	58.0	2.28	0.35	1.71	0.94	12.9	7.75	1.67
	1.0625	66.421	2.6150	23.812	0.9375	25.433	1.0013	19.050	0.7500	1.6	0.06	1.2	0.05	83.8	75.2	11.2		2688	2631	13.9	0.55	35.0	1.38	33.0	1.30	58.0	2.28	60.0	2.36	0.25	2.36	1.30	19.5	8.45	2.30
28.575	1.1250	57.150	2.2500	17.462	0.6875	17.462	0.6875	13.495	0.5313	3.6	0.14	1.6	0.06	47.2	42.7	6.10		15590	15520	12.7	0.50	39.0	1.54	33.5	1.32	51.0	2.01	53.0	2.0						